



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer DS25 68/1000

SPECfp_rate2000 = 21.5
SPECfp_rate_base2000 = 17.9

SPEC license #: 2 | Tested by: HP | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: Oct-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	239	15.5	2	197	18.8
171.swim	2	262	27.5	2	262	27.5
172.mgrid	2	354	11.8	2	236	17.7
173.applu	2	258	18.9	2	256	19.0
177.mesa	2	175	18.5	2	156	20.8
178.galgel	2	171	39.3	2	171	39.4
179.art	2	145	41.6	2	119	50.8
183.equake	2	393	7.67	2	156	19.4
187.facerec	2	177	24.9	2	171	25.7
188.amp	2	371	13.8	2	314	16.2
189.lucas	2	235	19.8	2	197	23.6
191.fma3d	2	305	16.0	2	241	20.2
200.sixtrack	2	268	9.51	2	245	10.4
301.apsi	2	382	15.8	2	386	15.6

Hardware

CPU: Alpha 21264C
 CPU MHz: 1000
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1 to 2
 Parallel: No
 Primary Cache: 64KB(I)+64KB(D) on chip
 Secondary Cache: 8MB off chip per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 8GB
 Disk Subsystem: 18.2GB SCSI
 Other Hardware: None

Software

Operating System: Tru64 UNIX V5.1A
 Compiler: Compaq C V6.4-215-46B70
 Program Analysis Tools V2.0
 Spike V5.2 DTK (1.471.2.2 46B5P)
 Compaq Fortran V5.4A-1472-46B2F
 Compaq Fortran 77 V5.4A-196-46B2F
 KAP Fortran V4.3 000607
 KAP Fortran 77 V4.1 980926
 KAP C V4.1 000607

File System: AdvFS
 System State: Multi-user

Notes/Tuning Information

Baseline C: cc -arch ev6 -fast -O4 ONESTEP
Fortran: f90 -arch ev6 -fast -O5 ONESTEP

Peak:

All use -g3 -arch ev6 -non_shared ONESTEP

Individual benchmark tuning:

168.wupwise: kf77 -fast -O4 -pipeline -unroll 2 +PFB
 171.swim: f90 -fast -O5
 172.mgrid: kf77 -O5 -transform_loops -tune ev6 -unroll 8
 173.applu: f90 -fast -O5 +PFB
 177.mesa: cc -fast -O4 +CFB +IFB
 178.galgel: f90 -fast -O5
 179.art: kcc -fast -O4 -unroll 10 -ckapargs='-arl=4
 -ur=4' +PFB
 183.equake: cc -fast -xtaso_short -assume
 restricted_pointers -all -ldensemalloc -none +PFB



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer DS25 68/1000

SPECfp_rate2000 = 21.5
SPECfp_rate_base2000 = 17.9

SPEC license #: 2 | Tested by: HP | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: Oct-2001

Notes/Tuning Information (Continued)

```

187.facerec: f90 -fast -O4 +PFB
188.amp: cc -fast -O4 -xtaso_short -assume
restricted_pointers
189.lucas: kf90 -O5 -fkapargs='-ur=1' +PFB
191.fma3d: kf90 -O4 -transform_loops +PFB
200.sixtrack: f90 -fast -O5 -assume accuracy_sensitive
-notransform_loops +PFB
301.apsi: kf90 -O5 -transform_loops -unroll 8
-fkapargs='-ur=1' +PFB

```

Most benchmarks are built using one or more types of profile-driven feedback. The types used are designated by abbreviations in the notes:

+CFB: Code generation is optimized by the compiler, using feedback from a training run. These commands are done before the first compile (in phase "fdo_pre0"):

```

mkdir /tmp/pp
rm -f /tmp/pp/${baseexe}*

```

and these flags are added to the first and second compiles:

```

PASS1_CFLAGS = -prof_gen_noopt -prof_dir /tmp/pp
PASS2_CFLAGS = -prof_use -prof_dir /tmp/pp

```

(Peak builds use /tmp/pp above; base builds use /tmp/pb.)

+IFB: Icache usage is improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_postN"):

```

mv ${baseexe} oldexe
spike oldexe -feedback oldexe -o ${baseexe}

```

+PFB: Prefetches are improved by the post-link-time optimizer Spike, using feedback from a training run. These commands are used (in phase "fdo_post_makeN"):

```

rm -f *Counts*
mv ${baseexe} oldexe
pixie -stats dstride oldexe 1>pixie.out 2>pixie.err
mv oldexe.pixie ${baseexe}

```

A training run is carried out (in phase "fdo_runN"), and then this command (in phase "fdo_postN"):

```

spike oldexe -fb oldexe -stride_prefetch -o ${baseexe}

```

When Spike is used for both Icache and Prefetch improvements, only one spike command is actually issued, with the Icache options followed by the Prefetch options.

Portability: galgel: -fixed



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
hp AlphaServer DS25 68/1000

SPECfp_rate2000 = 21.5
SPECfp_rate_base2000 = 17.9

SPEC license #: 2 | Tested by: HP | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: Oct-2001

Notes/Tuning Information (Continued)

Spike, and the Program Analysis Tools, are part of the Developers' Tool Kit Supplement, <http://www.tru64unix.compaq.com/dtk/>. The features used in this SPEC submission will be available at the web site as a production release in October, 2001. The C compiler for this SPEC submission has been available at the same location, as a production release, since August, 2001.