



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.8 GHz, Pentium 4 processor)

SPECfp2000 = 929

SPECfp_base2000 = 915

SPEC license #: 13 Tested by: Intel Corporation Test date: Jun-2002 Hardware Avail: Aug-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	132	1209	132	1215	
171.swim	3100	220	1408	217	1430	
172.mgrid	1800	212	850	209	859	
173.applu	2100	222	947	215	979	
177.mesa	1400	131	1070	130	1075	
178.galgel	2900	228	1271	224	1297	
179.art	2600	492	528	475	548	
183.quake	1300	126	1033	120	1081	
187.facerec	1900	168	1128	166	1143	
188.ammmp	2200	368	597	365	602	
189.lucas	2000	158	1266	158	1267	
191.fma3d	2100	222	946	221	949	
200.sixtrack	1100	216	509	212	520	
301.apsi	2600	377	690	377	690	

Hardware

CPU: Pentium 4 processor (2.8 GHz, 533 MHz bus)
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 8KBD on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 256 MB (2 128 MB PC800-40 RDRAM non-ECC modules)
 Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
 Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
 Compiler: Intel C++ Compiler 6.0 Build 020321Z
 Intel Fortran Compiler 6.0 Build 020321Z
 Microsoft Visual C++ 6.0 SP5(for libraries)
 File System: FAT32
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: -Qipo -Oa -QxW -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QxW -O3 +FDO
188.ammmp: -Qipo -QxW -O3 -Oa +FDO
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.8 GHz, Pentium 4 processor)

SPECfp2000 = 929

SPECfp_base2000 = 915

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO

301.apsi: -Qipo -QxW -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 8/2002:

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz