



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.0A GHz, Pentium 4 processor)

SPECint2000 = 759

SPECint_base2000 = 756

SPEC license #: 13 Tested by: Intel Corporation Test date: May-2002 Hardware Avail: May-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	168	831	168	832	
175.vpr	1400	290	483	290	482	
176.gcc	1100	123	894	123	892	
181.mcf	1800	317	568	317	568	
186.crafty	1000	129	775	130	766	
197.parser	1800	249	723	249	723	
252.eon	1300	152	855	142	918	
253.perlbmk	1800	197	913	198	911	
254.gap	1100	112	979	112	979	
255.vortex	1900	149	1278	150	1269	
256.bzip2	1500	248	604	247	607	
300.twolf	3000	584	514	585	513	

Hardware

CPU: Pentium 4 processor (2.0A GHz, 400 MHz bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 256 MB (2 128 MB PC800-40 RDRAM non-ECC modules)
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
Compiler: Intel C++ Compiler 6.0 Build 020321Z
Intel Fortran Compiler 6.0 Build 020321Z
Microsoft Visual C++ 6.0 SP5(for libraries)
File System: FAT32
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -QxW -Qipo -O3 +FDO

Base tuning for C++ programs: -QxW -Qipo -GX -GR

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -QxW -Qipo -Oa -O3 +FDO

175.vpr: -QxW -Qwp_ipo -O3 +FDO

176.gcc: -QxW -Qipo -O3 +FDO

181.mcf: -QxW -Qipo -O3 +FDO

186.crafty: -QxW -Qipo -Oa -O3 +FDO

197.parser: -QxW -Qipo -O3 +FDO

252.eon: -QxW -Qipo -O3 +FDO

253.perlbmk: -QxW -Qipo -O3 +FDO

254.gap: -QxW -Qipo -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 8/2002:

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.0A GHz, Pentium 4 processor)

SPECint2000 = 759

SPECint_base2000 = 756

SPEC license #: 13 | Tested by: Intel Corporation | Test date: May-2002 | Hardware Avail: May-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 400 MHz