



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Netra 20 (1200 MHz)

SPECint2000 = 712
SPECint_base2000 = 637

SPEC license #: 6 Tested by: Sun Microsystems Test date: Mar-2003 Hardware Avail: Apr-2003 Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	295	474	240	583	
175.vpr	1400	257	544	239	587	
176.gcc	1100	163	674	153	720	
181.mcf	1800	263	684	214	839	
186.crafty	1000	151	660	130	771	
197.parser	1800	318	565	274	656	
252.eon	1300	171	762	163	796	
253.perlbmk	1800	283	636	276	652	
254.gap	1100	238	462	206	533	
255.vortex	1900	192	992	170	1121	
256.bzip2	1500	217	691	202	744	
300.twolf	3000	460	652	423	709	

Hardware

CPU: UltraSPARC III Cu
 CPU MHz: 1200
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1-2
 Parallel: No
 Primary Cache: 32KBI+64KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: None
 Other Cache: None
 Memory: 4GB 4-way interleaved
 Disk Subsystem: 2 x 18GB SEAGATE ST318304FC
 Other Hardware: None

Software

Operating System: Solaris 9 4/03
 Compiler: Sun ONE Studio 8 (pre-FCS build 3/9)
 Sun Performance Library 8 (pre-FCS build 3/9)
 File System: ufs with ufs logging
 System State: Multi-User

Notes/Tuning Information

Compiler invocation:

```
C: cc
CXX: CC
F90: f90
F77: f90
```

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes and feedback for all benchmarks

```
164.gzip: -xO4 -xbuiltin=%all -xtarget=native -xalias_level=std
          -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100
175.vpr: -fast -xalias_level=std -xipo=2
          -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100 -lmopt -lm
176.gcc: -fast -xipo=2 -l12amm
181.mcf: -fast -xipo=2 -xprefetch_level=3 -Wc,-Qeps:enabled=1
186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
            Feedback adds -xlinkopt in PASS2
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Netra 20 (1200 MHz)

SPECint2000 = 712
SPECint_base2000 = 637

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Mar-2003 | Hardware Avail: Apr-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

```

197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -xalias_level=compatible -noex
            -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
253.perlbnk: -xO5 -xtarget=native -xipo -xalias_level=std -xsafe=mem
            -Wc,-Qeps:enabled=1,-Qeps:ws=8,-Qiselect-sw_pf_tbl_th=20,
            -Qiselect-funcalign=32,-Qicache-chbab=1
254.gap:    -fast -xipo=2 -xalias_level=strong -xvector
            -xprefetch_level=3 -W2,-Abcopy
255.vortex: -fast -xrestrict -xipo=2
            -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
            -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:    -xprofile=collect:./feedback
PASS2:    -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

default
autoup=900
tune_t_fsflushr=1

```

System Settings:

2nd CPU physically removed from the system