



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Altix 3000 (900MHz, Itanium 2)

SPECint_rate2000 = 389

SPECint_rate_base2000 = 389

SPEC license #: 4 | Tested by: SGI | Test date: Mar-2003 | Hardware Avail: Feb-2003 | Software Avail: Mar-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	64	279	372	64	279	372
175.vpr	64	304	342	64	304	342
176.gcc	64	182	449	64	182	449
181.mcf	64	498	268	64	498	268
186.crafty	64	163	456	64	163	456
197.parser	64	468	285	64	468	285
252.eon	64	176	548	64	176	548
253.perlbnk	64	324	413	64	324	413
254.gap	64	231	354	64	231	354
255.vortex	64	250	564	64	250	564
256.bzip2	64	314	355	64	314	355
300.twolf	64	598	372	64	598	372

Hardware

CPU: Intel Itanium 2
 CPU MHz: 900
 FPU: Integrated
 CPU(s) enabled: 64 cores, 64 chips, 1 core/chip
 CPU(s) orderable: 4-64
 Parallel: No
 Primary Cache: 16KBI + 16KBD (on chip) per CPU
 Secondary Cache: 256KB (on chip) per CPU
 L3 Cache: 1.5MB (on chip) per CPU
 Other Cache: N/A
 Memory: 128 GB (16*512MB DIMMS per 4cpu module)
 Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
 Other Hardware: None

Software

Operating System: SGI ProPack(TM) v2.1
 Compiler: Intel(R) C++ Compiler for Linux 7.1 (Build 20030307)
 File System: xfs
 System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -ipo -O3 +FDO
 C++ programs: -ipo -O2 +FDO -ansi_alias

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
 186.crafty: -DLINUX_i386
 252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST
 253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
 254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
 -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
 255.vortex: -DSPEC_CPU2000_LP64

Processes were bound to CPUs using dplace.

Peak flags same as baseline (basepeak=true set globally).