



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER250 (1100MHz)

SPECfp2000 = **1030**
SPECfp_base2000 = **866**

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: May-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	365	439	163	984
171.swim	3100	229	1351	169	1834
172.mgrid	1800	227	794	198	907
173.applu	2100	312	673	232	904
177.mesa	1400	343	408	262	534
178.galgel	2900	197	1474	169	1711
179.art	2600	42.7	6095	42.5	6117
183.earth	1300	84.3	1543	72.8	1786
187.facerec	1900	184	1031	166	1143
188.amp	2200	476	462	406	541
189.lucas	2000	214	933	219	915
191.fma3d	2100	324	648	302	694
200.sixtrack	1100	309	356	308	358
301.apsi	2600	359	725	359	725

Hardware

CPU: SPARC64 V
 CPU MHz: 1100
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1 to 2 (increments of 1)
 Parallel: None
 Primary Cache: 128KBI+128KBD on chip
 Secondary Cache: 1MB(I+D) on chip
 L3 Cache: None
 Other Cache: None
 Memory: 8192MB
 Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)
 Other Hardware: None

Software

Operating System: Solaris8 2/02 with current patches (see notes)
 Compiler: Fujitsu Parallelnavi 2.1 with patch 912528-02
 Sun ONE Studio 8 (EA2 version of Sun ONE Studio 8 used)
 Sun Performance Library 8
 File System: ufs
 System State: multi user

Notes/Tuning Information

```
FDO: (for Parallelnavi 2.1)
  fdo_pre0=rm -rf `pwd`/*.f.d
  PASS1=-Kpg PASS2=-Kpu
FDO: (for Sun ONE Studio 8)
  fdo_pre0=rm -rf ./feedback.profile ./SunWS_cache
  PASS1=-xprofile=collect:./feedback
  PASS2=-xprofile=use:./feedback
Baseline:
(using Fortran compiler of Sun ONE Studio 8 EA2)
  -fast -xtarget=ultra3 -lprism32 FDO
(using C compiler of Sun ONE Studio 8 EA2)
  -fast -xtarget=ultra3 -xipo=2 FDO ONESTEP=yes
Peak:
(for Parallelnavi 2.1)
168.wupwise: -fs -Kfast_GP2=2,largepage -O5 -x dir=./
  -Kpreex,prefetch_infer,alignl=64,preschedule_length=17 FDO
172.mgrid: -fs -Kfast_GP2=2,largepage,GREG_SYSTEM -Kpreex,prefetch_line=6,commonpad=144,alignc=64 FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER250 (1100MHz)

SPECfp2000 = 1030

SPECfp_base2000 = 866

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: May-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

```

178.galgel: -fs -Kfast_GP2=2,largepage,GREG_SYSTEM -x dir=./
-Kpreex,prefetch_infer,prefetch=4,frecipro,unroll=2,commonpad=152,arraypad_const=11,alignl=64
-Am -Fixed -KFMADD -SSL2 FDO
189.lucas: -fs -Kfast_GP2=2,largepage,GREG_SYSTEM -O5
-Kpreex,prefetch_infer,prefetch_line=6,preschedule_length=70 FDO
191.fma3d: -fs -Kfast_GP2=2,largepage,GREG_SYSTEM -x dir=./ -x55
-Kpreex,prefetch_infer,prefetch=4 FDO
(using FORTRAN90 compiler of Sun ONE Studio 8 EA2)
171.swim: -fast -xchip=ultra3cu -xcache=128/64/2:1024/64/2 -xarch=v8plusb
-xpad=common:4002 -xprefetch=latx:2.2
-Option iropt -Atile:skewp,-Ainline:cs=700 -lprism32
173.applu: -fast -xchip=ultra3 -xcache=128/64/2:1024/64/2 -xarch=v8plusb
-xipo=2 -xprefetch=latx:0.6 FDO ONESTEP=yes

187.facerec: -xO5 -xchip=ultra3 -xcache=128/64/2:1024/64/2 -xarch=v8plus
-xprefetch=yes -xprefetch_level=1 -xprefrtch=latx:2.0 -xvector=no -xdepend -ftrap=%none
-fns -fsimple=2 -lprism32 FDO ONESTEP=yes
200.sixtrack:-fast -xchip=ultra3 -xcache=128/64/2:1024/64/2 -xarch=v8plusb
-xipo=2 -lprism32 ONESTEP=yes
301.apsi: -fast -xchip=ultra3 -xcache=128/64/2:1024/64/2 -xarch=v8plusb
-xipo=2 -lprism32 FDO ONESTEP=yes

```

(using C compiler of Sun ONE Studio 8 EA2)

```

177.mesa: -fast -xchip=ultra2 -xcache=128/64/2:1024/64/2 -xarch=v8plusb -xipo=2 -xrestrict
-xalias_level=strong -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qms_pipe+unoovf FDO ONESTEP=yes
179.art: -fast -xchip=ultra3 -xcache=128/64/2:1024/64/2 -xarch=v8plusb -xipo=2 -xalias_level=std FDO ONESTEP=yes
183.equake: -fast -xchip=ultra3cu -xcache=128/64/2:1024/64/2 -xarch=v8plusb
-xalias_level=strong -xdepend -W2,-whole,-Amemopt:arrayloc -xprefetch
-Wc,-Qms_pipe-pref,-Qlp=1-av=512-t=6-fa=1-fl=1 -lprism32 -lmopt -lm FDO ONESTEP=yes
188.ammp: -fast -xchip=ultra3 -xcache=128/64/2:1024/64/2 -xarch=v8plusb
-xipo=2 -xrestrict -xalias_level=std -xdepend -xprefetch=latx:2.6 -lprism32 FDO ONESTEP=yes

```

Portability:

Base:

178.galgel: -e -fixed (for Sun ONE Studio 8 EA2)

Peak:

178.galgel: -Am -Fixed (for Parallelnavi 2.1)

Note:

System Tunables: (for /etc/system)

consistent_coloring=1,

shmsys:shminfo_shmmax=2147483648, shmsys:shminfo_shmmni=256,

shmsys:shminfo_shmseg=400,shminfo_shmmin=1

set tune_t_fsflushr = 86400

set autoup = 86400

(for /etc/opt/FJSVpnm/lpg.conf)

TSS=1024M, SHMSEGSIZE=256M

Shell Environments:

LD_LIBRARY_PATH="/opt3/SUNWspro/prod/lib/v8plusb"

PRISM_HEAP=268435456

PRISM_MODE=2

Feedback directed optimization was used except 171.swim(peak).

Small configuration memory system mode used ("4cpu mode", enabled via system console).

Stack size set to unlimited via "ulimit -s unlimited"

System board used with only one CPU present.

Sun ONE Studio 8 EA2 (Early Access 2), posted at URL <http://access1.sun.com/s1sprod8> as updated through 27-Mar-2003, was used for this submission.

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org>



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER250 (1100MHz)

SPECfp2000 = 1030
SPECfp_base2000 = 866

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: May-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

Sun ONE Studio 8 (final) will ship May-2003.

All patches for Solaris8 posted at

http://access1.sun.com/patch.public/cgi-bin/show_list.cgi/wrk/Sun_ONE_Studio_7_SPARC_SunOS_5.8
as of date 2003/04/21 were applied: 108434-11, 108435-11, 111697-04, 111721-03.