



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Workstation zx6000 (1500 MHz, Itanium 2)

SPECfp_rate2000 = 24.4

SPECfp_rate_base2000 = 24.4

SPEC license #: 3 Tested by: HP Fort Collins Test date: Jun-2003 Hardware Avail: Sep-2003 Software Avail: Sep-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	111	16.7	1	111	16.7
171.swim	1	74.0	48.6	1	74.0	48.6
172.mgrid	1	73.2	28.5	1	73.2	28.5
173.applu	1	60.8	40.0	1	60.8	40.0
177.mesa	1	123	13.2	1	123	13.2
178.galgel	1	68.8	48.9	1	68.8	48.9
179.art	1	38.3	78.7	1	38.3	78.7
183.quake	1	45.2	33.4	1	45.2	33.4
187.facerec	1	98.0	22.5	1	98.0	22.5
188.amp	1	156	16.3	1	156	16.3
189.lucas	1	115	20.2	1	115	20.2
191.fma3d	1	195	12.5	1	195	12.5
200.sixtrack	1	78.5	16.3	1	78.5	16.3
301.apsi	1	263	11.5	1	263	11.5

Hardware

CPU: Intel Itanium 2
 CPU MHz: 1500
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1-2
 Parallel: no
 Primary Cache: 16KBI + 16KBD (on chip) per CPU
 Secondary Cache: 256KB (on chip) per CPU
 L3 Cache: 6.0MB (on chip) per CPU
 Other Cache: N/A
 Memory: 12GB (12 * 1GB DIMMs)
 Disk Subsystem: 1x36GB 10k RPM SCSI disk
 Other Hardware: N/A

Software

Operating System: Red Hat Linux Advanced Workstation 2.1 (Update 2)
 Compiler: Intel C++ Compiler 7.1 for Linux64, Build 20030519
 Intel Fortran Compiler 7.1 for Linux64, Build 20030519
 File System: ext3
 System State: Multi-user

Notes/Tuning Information

```
+FDO: PASS1=-prof_gen PASS2=-prof_use
Base tuning flags:
    C programs: -ipo -O3 +FDO -ansi_alias
    Fortran programs: -ipo -O3 +FDO
Portability:
    178.galgel: -FI

Peak flags same as baseline (basepeak=true set globally)
```

Note:
 'ELILO boot: linux maxcpus=0' used to
 deconfigure other processors if necessary
 Kernel was built with the configuration of 64K page size.