



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 1750 (3.06 GHz Xeon)

SPECint_rate2000 = 14.4
SPECint_rate_base2000 = 13.8

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2003 | Hardware Avail: Jul-2003 | Software Avail: Apr-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	117	13.9	1	116	13.9
175.vpr	1	170	9.56	1	169	9.59
176.gcc	1	72.4	17.6	1	72.3	17.7
181.mcf	1	246	8.47	1	244	8.55
186.crafy	1	84.9	13.7	1	84.8	13.7
197.parser	1	158	13.2	1	158	13.2
252.eon	1	96.0	15.7	1	82.7	18.2
253.perlbnk	1	135	15.5	1	130	16.1
254.gap	1	70.6	18.1	1	70.6	18.1
255.vortex	1	104	21.2	1	104	21.2
256.bzip2	1	165	10.5	1	159	11.0
300.twolf	1	268	13.0	1	194	18.0

Hardware

CPU: Intel Pentium Xeon (533 MHz system bus)
 CPU MHz: 3066
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: 1024KB(I+D) on chip
 Other Cache: N/A
 Memory: 4 X 512MB DDR266
 Disk Subsystem: 1 x 17GB Ultra3 Seagate SCSI
 Other Hardware:

Software

Operating System: Windows 2000 Server (SP2)
 Compiler: Intel C++ Compiler 7.1 (20030402Z)
 Microsoft Visual Studio .NET (7.0.9466)
 MicroQuill SmartHeap Library 6.01
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafy: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

FEEDBACK DIRECTED OPTIMIZATION

FDO: PASS1= -Qprof_gen PASS2=-Qprof_use

BASE TUNING

C: -QxW -Qipo -O3 +FDO
 C++: -QxW -Qipo -GX -GR

PEAK TUNING

164.gzip: -QxW -Qipo -Oa -O3 +FDO
 175.vpr: -QxW -Qipo -O3 +FDO
 176.gcc: -QxW -Qipo -O3 +FDO
 181.mcf: -QxW -Qipo -O3 +FDO shlw32M.lib
 186.crafy: PASS1= -Qprof_gen PASS2= -Qipo -Qprof_use -QxW -O3
 197.parser: -QxW -Qipo -O3 +FDO
 252.eon: PASS1= -Qprof_gen PASS2= -Qipo -Qprof_use -QxW -O3
 253.perlbnk: -QxW -Qipo -O3 +FDO shlw32M.lib
 254.gap: basepeak=yes



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 1750 (3.06 GHz Xeon)

SPECint_rate2000 = 14.4
SPECint_rate_base2000 = 13.8

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2003 | Hardware Avail: Jul-2003 | Software Avail: Apr-2003

Notes/Tuning Information (Continued)

```
255.vortex    basepeak=yes
256.bzip2:    -Qipo -Oa -Qunroll1 +FDO
300.twolf:    -Qipo -QxW -O3 -Oa      shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 6.01
              www.microquill.com
ONESTEP=YES is set for all benchmarks
```