



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS V810

SPECfp2000 = 1397
SPECfp_base2000 = 1309

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: Nov-2003 Hardware Avail: Dec-2003 Software Avail: Dec-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	114	1400	105	1531	
171.swim	3100	174	1784	158	1956	
172.mgrid	1800	148	1218	147	1224	
173.applu	2100	191	1098	179	1172	
177.mesa	1400	90.8	1542	89.6	1563	
178.galgel	2900	149	1943	128	2263	
179.art	2600	176	1479	161	1616	
183.quake	1300	121	1078	98.7	1317	
187.facerec	1900	126	1503	123	1539	
188.amp	2200	165	1337	161	1365	
189.lucas	2000	128	1560	128	1560	
191.fma3d	2100	165	1276	165	1276	
200.sixtrack	1100	207	532	185	596	
301.apsi	2600	204	1276	194	1338	

Hardware

CPU: AMD Opteron (TM) 248 (2.2 GHz)
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x1GB PC2700 DDR SDRAM CL2.5, ECC Registered
 Disk Subsystem: ATA-100
 Other Hardware: None

Software

Operating System: Windows XP Pro SP1
 Compiler: Intel C/C++ 7.0 build 20021212Z and Intel Fortran 7.0 build 20021212Z
 Compaq Visual Fortran Compiler Version 6.6 (Update B)
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 6.0
 File System: FAT32
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
icl and ifl are the Intel C/C++ and Fortran compilers
f90 is the Compaq Fortran compiler
shlw32M6.lib is the SmartHeap library V6.0 from MicroQuill www.microquill.com
Portability:
  178.galgel: -FI -Fe$@ -link -stack:32000000
Baseline: C          icl +FDO -O3 -QxW -Qipo
Peak tuning:
Baseline: Fortran   ifl +FDO -O3 -QxW -Qipo
  168.wupwise:      ifl +FDO -O3 -QxK -Qipo -Ow
  171.swim:         f90 -Optimize:5 -alignment:dcommons -alignment:records
                   -alignment:sequence -architecture:k7
                   -assume:noaccuracy_sensitive -math_library:fast -tune:k7
  172.mgrid:        ifl +FDO -O3 -QaxW -Qipo -Oa -Qprefetch-
  173.applu:         ifl +FDO -O3 -QxK -Qipo -Qscalar_rep- -Zp8
  177.mesa:          icl +FDO -O3 -QxW -Qipo -Oa -Qscalar_rep-
  178.galgel:       f90 -Optimize:5 -fast
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS V810

SPECfp2000 = 1397
SPECfp_base2000 = 1309

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2003 | Hardware Avail: Dec-2003 | Software Avail: Dec-2002

Notes/Tuning Information (Continued)

```

179.art:          icl          -Qipo -Oa          -Qunroll14 -Zp4
183.earthquake:  icl          -O3 -QxK  -Qipo -Oa  shlw32M6.lib -Zp4
187.facerec:     ifl +FDO -O3 -QaxW -Qipo          -Qscalar_rep- -Qunroll11
188.amm:         icl          -QxW          -Oa
189.lucas:       ifl +FDO -O3 -QxW  -Qipo          -Qprefetch-
191.fma3d:       ifl basepeak=1
200.sixtrack:    ifl          -Qipo -Oa          -Zp4
301.apsi:        f90 -Optimize:5 -fast

```

System tested with only one CPU present.
 BIOS default settings have been used. These include:
 ECC memory checking disabled,
 node interleave disabled, SRAT enabled.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>