



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E4900 (12 processor)

SPECint_rate2000 = 175
SPECint_rate_base2000 = 156

SPEC license #: 6 Tested by: Sun Microsystems Test date: Apr-2004 Hardware Avail: Mar-2004 Software Avail: Apr-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	24	334	117	24	282	138
175.vpr	24	281	139	24	268	145
176.gcc	24	203	151	24	179	171
181.mcf	24	303	165	24	258	194
186.crafty	24	165	169	24	137	203
197.parser	24	345	145	24	306	164
252.eon	24	178	203	24	170	213
253.perlbnk	24	304	165	24	279	180
254.gap	24	322	95.2	24	255	120
255.vortex	24	210	251	24	188	281
256.bzip2	24	247	169	24	230	182
300.twolf	24	539	155	24	524	159

Hardware

CPU: UltraSPARC s400
 CPU MHz: 1200
 FPU: Integrated
 CPU(s) enabled: 24 cores, 12 chips, 2 cores/chip
 CPU(s) orderable: 4, 8, 12 (order by # chips)
 Parallel: No
 Primary Cache: 32KBI+64KBD per core on chip (64KBI+128KBD on chip)
 Secondary Cache: 8MB(I+D) per core off chip (16MB(I+D) off chip)
 L3 Cache: None
 Other Cache: None
 Memory: 48GB 16-way interleaved
 Disk Subsystem: Sun StorEdge S1 Disk Array (2x36GB)
 Sun StorEdge T3 Array for the Workgroup (9x36GB)
 Other Hardware: None

Software

Operating System: Solaris 9 04/04
 Compiler: Sun ONE Studio 8
 Sun Performance Library 8
 File System: ufs with ufs logging
 System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes and feedback for all benchmarks

164.gzip: -xO4 -xbuiltin=%all -xtarget=native -xalias_level=std
 -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100
 175.vpr: -fast -xalias_level=std -xipo=2
 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100 -lmopt -lm
 176.gcc: -fast -xipo=2 -l12amm
 181.mcf: -fast -xipo=2 -xprefetch_level=2 -Wc,-Qeps:enabled=1
 186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E4900 (12 processor)

SPECint_rate2000 = 175
SPECint_rate_base2000 = 156

SPEC license #: 6 Tested by: Sun Microsystems Test date: Apr-2004 Hardware Avail: Mar-2004 Software Avail: Apr-2004

Notes/Tuning Information (Continued)

```

Feedback adds -xlinkopt in PASS2
197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    -fast -xipo=2 -xalias_level=compatible -noex
            -Qoption cg -Qeps:enabled=1,-Qeps:ws=32
253.perlbnk: -xO5 -xtarget=native -xipo -xalias_level=std -xsafe=mem
            -Wc,-Qeps:enabled=1,-Qeps:ws=8,-Qiselect-sw_pf_tbl_th=20,
            -Qiselect-funcalign=32,-Qicache-chbab=1
254.gap:    -fast -xipo=2 -xalias_level=strong -xvector
            -xprefetch_level=3 -W2,-Abcopy
255.vortex: -fast -xrestrict -xipo=2
            -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
            -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
256.bzip2:  -fast -xipo -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

Processes were bound to CPUs using submit=pbind

The system was configured with multiple file systems.
The O/S was installed on one disk of the Sun StorEdge S1
Disk Array (ufs, ufs w/logging). The benchmark was run on
the Sun StorEdge T3 Array, using H/W Raid 5 and ufs with
ufs logging file system.