



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Altix 350 (1400MHz/3MB, Itanium 2)

SPECint_rate2000 = --

SPECint_rate_base2000 = 24.7

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2004 | Hardware Avail: May-2004 | Software Avail: Jun-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	162	20.1			
175.vpr	2	160	20.3			
176.gcc	2	92.9	27.5			
181.mcf	2	172	24.3			
186.crafty	2	91.3	25.4			
197.parser	2	223	18.7			
252.eon	2	92.0	32.8			
253.perlbnk	2	173	24.1			
254.gap	2	141	18.1			
255.vortex	2	111	39.8			
256.bzip2	2	148	23.5			
300.twolf	2	237	29.3			

Hardware

CPU: Intel Itanium 2
 CPU MHz: 1400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 2-16
 Parallel: No
 Primary Cache: 16KBI + 16KBD (on chip) per core
 Secondary Cache: 256KB (on chip) per core
 L3 Cache: 3.0MB (on chip) per core
 Other Cache: N/A
 Memory: 8 GB (16*512MB PC2100 DIMMS per 2core module)
 Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
 Other Hardware: None

Software

Operating System: SGI ProPack(TM) v3.0
 Compiler: Intel(R) C++ Compiler for Linux 8.0 (Build 20040318)
MicroQuill SmartHeap Library 7.01 (www.microquill.com)
 File System: xfs
 System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -fast -auto_ilp32 +FDO
 C++ programs: -fast -ansi_alias +FDO
 Extra Libraries: libsmartheap64.a

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca
 186.crafty: -DLINUX_i386
 252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST -DFMAX_IS_DOUBLE
 253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
 254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
 -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
 255.vortex: -DSPEC_CPU2000_LP64 srcalt=closed_files

Processes were bound to CPUs using dplace.