



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

## Intel Corporation

Intel D925XECV2 motherboard(3.46 GHz, Intel Pentium 4 processor with HT Technology Extreme Edition)

SPECfp2000 = 1724

SPECfp\_base2000 = 1719

SPEC license #: 13 Tested by: Intel Corporation Test date: Oct-2004 Hardware Avail: Nov-2004 Software Avail: Sep-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	74.1	2159	74.2	2156	
171.swim	3100	124	2505	124	2503	
172.mgrid	1800	118	1526	118	1526	
173.applu	2100	143	1468	144	1459	
177.mesa	1400	90.9	1540	90.9	1540	
178.galgel	2900	87.3	3324	87.3	3324	
179.art	2600	99.5	2613	99.5	2613	
183.quake	1300	69.5	1869	69.5	1869	
187.facerec	1900	100	1894	100	1895	
188.amp	2200	163	1347	158	1392	
189.lucas	2000	101	1981	101	1979	
191.fma3d	2100	143	1468	143	1468	
200.sixtrack	1100	164	670	162	678	
301.apsi	2600	199	1308	199	1308	

### Hardware

CPU: Intel Pentium 4 processor with HT Technology Extreme Edition(3.46 GHz, 1066 MHz bus)  
CPU MHz: 3466  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip with HT Technology enabled  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 12k micro-ops I + 8KBD on chip  
Secondary Cache: 512KB(I+D) on chip  
L3 Cache: 2MB(I+D) on chip  
Other Cache: N/A  
Memory: 1 GB (2x512MB PC2-4300 DDRII 533 CL4-4-4)  
Disk Subsystem: Seagate ST3160023AS 160 GB Serial ATA (7200 RPM, 8MB cache)  
Other Hardware: N/A

### Software

Operating System: Windows XP Professional SP2  
Compiler: Intel C++ and Fortran Compiler 8.1 Build 20040802Z  
Microsoft Visual Studio .Net 2002(for libraries)  
SmartHeap Library Version 6.0 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -O3 -Qipo -QxN +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -O3 -Qipo -QxN -Qansi_alias +FDO
171.swim: -O3 -Qipo -QxN -Qansi_alias +FDO
172.mgrid: -O3 -Qipo -QxN -Qansi_alias +FDO
173.applu: -O3 -Qipo -QxN -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -O3 -Qipo -QxN -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: basepeak=yes
187.facerec: -O3 -Qipo -QxN -Qunroll11 -Qscalar_rep- +FDO
188.amp: -Oa -QxN
189.lucas: -O3 -Qipo -QxN -Qprefetch- +FDO
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

## Intel Corporation

Intel D925XECV2 motherboard(3.46 GHz, Intel Pentium 4 processor with HT Technology Extreme Edition)

SPECfp2000 = 1724

SPECfp\_base2000 = 1719

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2004 | Hardware Avail: Nov-2004 | Software Avail: Sep-2004

### Notes/Tuning Information (Continued)

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxN +FDO

301.apsi: -O3 -Qipo -QxN +FDO

Tested systems can be used with Shin-G ATX case, Antec power supply NeoPower 480

Product description located as of Nov-2004:

[http://www.intel.com/design/motherbd/cv2/index.htm?iid=ipp\\_browse+motherbd\\_d925xecv2&](http://www.intel.com/design/motherbd/cv2/index.htm?iid=ipp_browse+motherbd_d925xecv2&)

Motherboard is available through Intel Reseller Channel:

[http://www.intel.com/cd/channel/reseller/asm-na/eng/products/box\\_desktop\\_boards/intel\\_boards/p4\\_boards/p4\\_dsk\\_board\\_D925XECV2/index.htm](http://www.intel.com/cd/channel/reseller/asm-na/eng/products/box_desktop_boards/intel_boards/p4_boards/p4_dsk_board_D925XECV2/index.htm)

The system bus runs at 1066 MHz

sh1w32M.lib is the SmartHeap library V6.0 from <http://www.microquill.com/smartheap/index.html>

A PCIe-16 video card is installed and HT Technology is enabled

Memory DIMMs used: Micron MT16HTF6464AG-53EB2