



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP Integrity rx1620-2 (1.3GHz/3MB, Itanium 2)

SPECfp_rate2000 = 25.7
SPECfp_rate_base2000 = 25.7

SPEC license #: 3 Tested by: HP Richardson Test date: Dec-2004 Hardware Avail: Jan-2005 Software Avail: Nov-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	61.6	30.1	1	61.6	30.1
171.swim	1	74.7	48.2	1	74.7	48.2
172.mgrid	1	75.3	27.7	1	75.3	27.7
173.applu	1	62.2	39.1	1	62.2	39.1
177.mesa	1	138	11.8	1	138	11.8
178.galgel	1	54.8	61.4	1	54.8	61.4
179.art	1	25.5	118	1	25.5	118
183.equake	1	45.0	33.5	1	45.0	33.5
187.facerec	1	128	17.2	1	128	17.2
188.amp	1	181	14.1	1	181	14.1
189.lucas	1	120	19.4	1	120	19.4
191.fma3d	1	152	16.1	1	152	16.1
200.sixtrack	1	85.7	14.9	1	85.7	14.9
301.apsi	1	281	10.7	1	281	10.7

Hardware

CPU: Intel Itanium 2 (1.3GHz/3MB, 400MHz FSB)
 CPU MHz: 1300
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1-2
 Parallel: no
 Primary Cache: 16KBI + 16KBD on chip, per core
 Secondary Cache: 256KB (I+D) on chip, per core
 L3 Cache: 3.0MB (I+D) on chip, per core
 Other Cache: N/A
 Memory: 16GB (8x2GB DIMMs)
 Disk Subsystem: 1x36GB 15K SCSI
 Other Hardware: N/A

Software

Operating System: Red Hat Linux Advanced Server release 3.0AS (Update 3)
 Compiler: Intel C++ Compiler 8.1 for Linux (Build 20041021)
 Intel Fortran Compiler 8.1 for Linux (Build 20041021)
 File System: ext3
 System State: Multi-user

Notes/Tuning Information

Base tuning flags:

C programs: -fast -ansi_alias +FDO -IPF_fp_relaxed
 Fortran programs: -fast +FDO -IPF_fp_relaxed

Portability:

178.galgel: -FI
 187.facerec: srcalt=AllocShape

Peak flags same as baseline (basepeak=true set globally)

+FDO: PASS1=-prof_gen PASS2=-prof_use

Note:

EFI command "cpuconfig" used prior to booting to
 deconfigure other processors if necessary