



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP Integrity rx2620-2 (1.3GHz/3MB, Itanium 2)

SPECfp_rate2000 = 42.7
SPECfp_rate_base2000 = 42.7

SPEC license #: 3 Tested by: HP Richardson Test date: Dec-2004 Hardware Avail: Dec-2004 Software Avail: Nov-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	74.8	49.7	2	74.8	49.7
171.swim	2	154	46.7	2	154	46.7
172.mgrid	2	125	33.4	2	125	33.4
173.applu	2	66.4	73.4	2	66.4	73.4
177.mesa	2	137	23.8	2	137	23.8
178.galgel	2	65.6	102	2	65.6	102
179.art	2	25.9	233	2	25.9	233
183.equake	2	60.4	49.9	2	60.4	49.9
187.facerec	2	143	30.9	2	143	30.9
188.amp	2	183	27.8	2	183	27.8
189.lucas	2	160	29.0	2	160	29.0
191.fma3d	2	175	27.9	2	175	27.9
200.sixtrack	2	86.4	29.5	2	86.4	29.5
301.apsi	2	294	20.5	2	294	20.5

Hardware

CPU: Intel Itanium 2 (1.3 GHz/3MB, 400 MHz FSB)
CPU MHz: 1300
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1-2
Parallel: no
Primary Cache: 16KBI + 16KBD on chip, per core
Secondary Cache: 256KB (I+D) on chip, per core
L3 Cache: 3.0MB (I+D) on chip, per core
Other Cache: N/A
Memory: 24GB (12x2GB DIMMs)
Disk Subsystem: 1x36GB 15K SCSI
Other Hardware: N/A

Software

Operating System: Red Hat Linux Advanced Server release 3.0AS (Update 3)
Compiler: Intel C++ Compiler 8.1 for Linux (Build 20041021)
Intel Fortran Compiler 8.1 for Linux (Build 20041021)
File System: ext3
System State: Multi-user

Notes/Tuning Information

Base tuning flags:

C programs: -fast -ansi_alias +FDO -IPF_fp_relaxed
Fortran programs: -fast +FDO -IPF_fp_relaxed

Portability:

178.galgel: -FI
187.facerec: srcalt=AllocShape

Peak flags same as baseline (basepeak=true set globally)

+FDO: PASS1=-prof_gen PASS2=-prof_use

Note:

EFI command "cpuconfig" used prior to booting to
deconfigure other processors if necessary