



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R710 (3.6 GHz Intel Xeon)

SPECint_rate2000 = 34.1
SPECint_rate_base2000 = 34.0

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Mar-2005 | Hardware Avail: Mar-2005 | Software Avail: Mar-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	119	27.4	2	119	27.2
175.vpr	2	157	20.6	2	153	21.3
176.gcc	2	62.0	41.1	2	62.0	41.1
181.mcf	2	214	19.6	2	214	19.6
186.crafty	2	74.7	31.1	2	75.0	30.9
197.parser	2	135	30.9	2	135	30.9
252.eon	2	57.5	52.5	2	57.2	52.7
253.perlbnk	2	88.2	47.3	2	87.8	47.6
254.gap	2	64.4	39.6	2	64.4	39.6
255.vortex	2	72.5	60.8	2	72.5	60.8
256.bzip2	2	152	22.9	2	149	23.3
300.twolf	2	174	40.0	2	175	39.7

Hardware

CPU: Intel Xeon (3.6 GHz, 1MB L2, 800MHz system bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 6x512MB ECC DDR2-400 SDRAM
Disk Subsystem: 1 x 36GB 10000RPM U320 SCSI HDD
Other Hardware:

Software

Operating System: Windows2003 Enterprise Edition (Build 3790)
Compiler: Intel C++ Compiler 8.1 Build 20041019Z
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R710 (3.6 GHz Intel Xeon)

SPECint_rate2000 = 34.1
SPECint_rate_base2000 = 34.0

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Mar-2005 | Hardware Avail: Mar-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO
300.twolf: -fast -O3 +FDO shlw32M.lib
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
Product description located as of Apr-2005:
<http://www.acer.com>