



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R510 (3.0 GHz Intel Xeon)

SPECint_rate2000 = 28.8
SPECint_rate_base2000 = 28.8

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2005 | Hardware Avail: May-2005 | Software Avail: Oct-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	141	23.0	2	141	23.0
175.vpr	2	181	17.9	2	178	18.3
176.gcc	2	72.5	35.2	2	72.5	35.2
181.mcf	2	232	18.0	2	232	18.0
186.crafty	2	90.0	25.8	2	90.0	25.8
197.parser	2	162	25.7	2	162	25.8
252.eon	2	68.9	43.8	2	68.7	43.9
253.perlbnk	2	106	39.3	2	106	39.4
254.gap	2	76.0	33.6	2	76.0	33.6
255.vortex	2	89.7	49.1	2	89.7	49.1
256.bzip2	2	174	20.0	2	175	19.9
300.twolf	2	214	32.6	2	212	32.8

Hardware

CPU: Intel Xeon (3.0 GHz, 1MB L2, 800MHz system bus)
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology disabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 6 x 512MB ECC DDR-333 SDRAM
 Disk Subsystem: 1 x 80GB 7200RPM SATA HDD
 Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
 Compiler: Intel C++ Compiler 8.1 Build 20041019Z
 Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)
 SmartHeap Library Version 7.4 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R510 (3.0 GHz Intel Xeon)

SPECint_rate2000 = 28.8

SPECint_rate_base2000 = 28.8

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: May-2005 | Hardware Avail: May-2005 | Software Avail: Oct-2004

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO
300.twolf: -fast -O3 +FDO shlw32M.lib
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
Product description located at <http://www.acer.com>