




# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL25p (AMD Opteron (TM) 275)

SPECfp\_rate2000 = 28.2  
SPECfp\_rate\_base2000 = 27.0

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2005 Hardware Avail: Jun-2005 Software Avail: Jun-2005



### Hardware

CPU: AMD Opteron (TM) 275  
 CPU MHz: 2200  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD on chip  
 Secondary Cache: 1024KB(I+D) on chip per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x2048MB PC3200 CL3.0  
 Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI  
 Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise SP1  
 Compiler: Intel C++ Compiler 8.0 Build 20040318Z  
 Intel Fortran Compiler for 32-bit applications 8.1 build 20050517Z  
 PGI Fortran compiler 6.0-4 for Windows XP (32-bit)  
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
 MicroQuill Smartheap Library 7.0  
 AMD Core Math Library V2.6.0  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
+ACML is linking with AMD Core Math Library V2.6.0
ONESTEP is set for all peak runs.
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran compiler.
The Intel C++ 8.0 and the Intel Fortran 8.1 compilers are setup in the following order:
"c:\program files\intel\fortran\compiler80\ia32\bin\ifortvars.bat"
"c:\program files\intel\cpp\compiler80\ia32\bin\iclvars.bat"
To make sure that the correct libraries are selected, the following link option is
added for the peak runs where Intel Fortran 8.1 compiler is used:
LDOPT = -Fe$@ -link -LIBPATH:"c:\program files\intel\fortran\compiler80\ia32\lib"
(denoted by +LIBPATH:INTEL8.1 in the optimization flags listed below)
Base tuning for C programs: icl -fast -arch:SSE2 -QaxW +FDO
Base tuning for FORTRAN programs: pgf90 -fastsse -Mipa=fast,inline
Portability flags:
178.galgel: -Mfixed
Peak tuning:
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL25p (AMD Opteron (TM) 275)

SPECfp\_rate2000 = 28.2  
SPECfp\_rate\_base2000 = 27.0

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2005 Hardware Avail: Jun-2005 Software Avail: Jun-2005

## Notes/Tuning Information (Continued)

```

168.wupwise:      pgf90 basepeak=yes
171.swim:         ifort -Qipo -O3 -QaxN -QxW +FDO -Qunroll0      +LIBPATH:INTEL8.1
172.mgrid:       pgf90 basepeak=yes
173.applu:       ifort -Qipo -O3 -QaxN -QxW +FDO -auto      +LIBPATH:INTEL8.1
177.mesa:        icl -Qipo -arch:SSE2      +FDO -Qunroll1 -Qansi_alias
                 -Qoption,f,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
178.galgel:      pgf90 -fastsse -Mipa=fast,safe RM_SOURCES=lapak.f90 -Munix +ACML
179.art:         icl -Qipo      -Zp4 +FDO
183.equake:      icl basepeak=yes
187.facerec:     ifort -Qipo      -QxW +FDO -Qunroll3      +LIBPATH:INTEL8.1
                 -Qoption,f,-ip_ninl_max_stats=2500,-ip_ninl_max_total_stats=7000
188.ammp:        icl -Oa -arch:SSE2 -Zp4      -Qansi_alias
189.lucas:       ifort -Qipo      -QxW      -Qunroll1      +LIBPATH:INTEL8.1
191.fma3d:       ifort -Qipo      -QaxN -QxW +FDO -Qansi-alias- +LIBPATH:INTEL8.1
200.sixtrack:    pgf90 basepeak=yes
301.apsi:        pgf90 basepeak=yes

```

BIOS Configuration Notes  
Node Interleaving is Disabled