



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML370 G4 (3.8GHz, Intel Xeon)

SPECint2000 = 1800
SPECint_base2000 = 1785

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: May-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	112	1246	111	1261	
175.vpr	1400	115	1222	112	1252	
176.gcc	1100	52.5	2093	52.5	2093	
181.mcf	1800	89.5	2011	89.5	2012	
186.crafty	1000	71.1	1406	71.1	1406	
197.parser	1800	118	1531	117	1537	
252.eon	1300	55.8	2332	55.3	2350	
253.perlbmk	1800	84.0	2143	81.5	2209	
254.gap	1100	56.4	1951	55.5	1983	
255.vortex	1900	61.7	3080	61.8	3075	
256.bzip2	1500	113	1332	112	1340	
300.twolf	3000	158	1894	158	1894	

Hardware

CPU: Intel Xeon (3.8GHz, 2MB L2, 800MHz bus)
CPU MHz: 3800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1024MB PC2-3200
Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 8.1 Build 20050524Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib

Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -fast +FDO ONESTEP=yes

175.vpr: -fast +FDO ONESTEP=yes

176.gcc: basepeak = 1

181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib

186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

197.parser: -fast +FDO ONESTEP=yes

252.eon: -fast +FDO

253.perlbmk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

254.gap: -fast +FDO ONESTEP=yes

255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML370 G4 (3.8GHz, Intel Xeon)

SPECint2000 = 1800
SPECint_base2000 = 1785

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2005 Hardware Avail: Sep-2005 Software Avail: May-2005

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO ONESTEP=yes shlw32M.lib
300.twolf: -fast +FDO shlw32M.lib
BIOS Configuration Notes
Hyper-Threading Technology disabled