



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
X6DVA-4G2 Motherboard

SPECfp_rate2000 = 31.2

SPECfp_rate_base2000 = 30.8

SPEC license #01176 | Tested by: Supermicro | Test date: Sep-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	139	53.4	4	137	54.0
171.swim	4	595	24.2	4	580	24.8
172.mgrid	4	378	22.1	4	368	22.7
173.applu	4	414	23.6	4	403	24.2
177.mesa	4	165	39.3	4	165	39.3
178.galgel	4	265	50.9	4	260	51.7
179.art	4	316	38.2	4	316	38.2
183.quake	4	191	31.5	4	187	32.2
187.facerec	4	221	39.9	4	218	40.5
188.amp	4	403	25.3	4	395	25.9
189.lucas	4	392	23.7	4	383	24.3
191.fma3d	4	373	26.1	4	373	26.1
200.sixtrack	4	233	21.9	4	240	21.3
301.apsi	4	379	31.8	4	374	32.2

Hardware

CPU: Intel Xeon Processor (3.80 GHz, 2MB L2, 800 MHz bus)
CPU MHz: 3800
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology Enabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 6 x 2.0GB SMART DDR2 400MHz ECC
Disk Subsystem: 250GB Maxtor YAR51HWO SATA HDD
Other Hardware: N/A

Software

Operating System: Windows Server 2003 EE SP1
Compiler: Intel C++ and Fortran Compiler 9.0 Build 20050430Z (32-bit)
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
shlw32M.lib is the SmartHeap Library
Portability:
178.galgel: -FI /F32000000
191.fmma3d approved windowsdp src.alt used
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: -fast -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo shlw32M.lib +FDO
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
X6DVA-4G2 Motherboard

SPECfp_rate2000 = 31.2

SPECfp_rate_base2000 = 30.8

SPEC license #01176 | Tested by: Supermicro | Test date: Sep-2005 | Hardware Avail: Sep-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

188. ammp: -fast -Oa +FDO shlw32M.lib

189. lucas: -fast -Qprefetch- +FDO

191. fma3d: basepeak=yes

200. sixtrack: -Qipo -QxP +FDO

301. apsi: -fast +FDO

New 32-bit Windows tools used, approved in May-2005

Tested system was built with SC811S-420 Chassis.

Product description located as of:

<http://www.supermicro.com/products/motherboard/Xeon800/E7320/X6DVA-4G2.cfm>

The system bus runs at 800MHz