



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Supermicro X6DHR-TG Motherboard

SPECint\_rate2000 = 41.3

SPECint\_rate\_base2000 = 41.3

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Nov-2004 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	171	38.0	4	173	37.6
175.vpr	4	251	25.9	4	247	26.3
176.gcc	4	91.2	56.0	4	91.2	56.0
181.mcf	4	374	22.3	4	374	22.3
186.crafty	4	138	33.7	4	138	33.7
197.parser	4	202	41.3	4	202	41.4
252.eon	4	110	54.8	4	110	54.7
253.perlbnk	4	174	48.1	4	174	47.9
254.gap	4	115	44.4	4	115	44.4
255.vortex	4	131	67.4	4	131	67.4
256.bzip2	4	200	34.8	4	201	34.6
300.twolf	4	266	52.3	4	265	52.5

### Hardware

CPU: Intel Xeon 3.8GHz processor (3.8 GHz, 2MB L2, 800 MHz bus)  
CPU MHz: 3800  
FPU: Integrated  
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip(Hyper-Threading Technology Enabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12k micro-ops I + 16KBD on chip  
Secondary Cache: 2048KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8GB (8x1GB DDR333 ECC REG)  
Disk Subsystem: 1 X 40GB IDE  
Other Hardware: N/A

### Software

Operating System: Windows 2003 EE SP1  
Compiler: Intel C++ Compiler 9.0 Build 20050430Z (32-bit)  
Microsoft Visual Studio .Net 2003(for libraries)  
SmartHeap Library Version 7.4 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
shlw32M.lib is the SmartHeap Library
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDDL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro  
X6DHR-TG Motherboard

SPECint\_rate2000 = 41.3

SPECint\_rate\_base2000 = 41.3

SPEC license #01176 | Tested by: Supermicro | Test date: Oct-2005 | Hardware Avail: Nov-2004 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

255.vortex basepeak=yes  
256.bzip2: -fast -Oa -Qunroll1 +FDO  
300.twolf: -fast -O3 +FDO shlw32M.lib  
New 32-bit Windows tools used, approved in May-2005  
Tested system was built with SC813T-500 Chassis.  
Product description located as of:  
<http://www.supermicro.com/products/motherboard/Xeon800/E7520/X6DHR-TG.cfm>  
The system bus runs at 800MHz