



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX300 S2, 64-bit Intel Xeon 3.60 GHz

SPECfp_rate2000 = 22.1
SPECfp_rate_base2000 = 22.1

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	124	30.0	2	124	30.0
171.swim	2	252	28.5	2	252	28.5
172.mgrid	2	211	19.8	2	211	19.8
173.applu	2	293	16.6	2	293	16.6
177.mesa	2	174	18.7	2	174	18.7
178.galgel	2	185	36.3	2	185	36.3
179.art	2	160	37.8	2	160	37.8
183.quake	2	84.3	35.8	2	84.3	35.8
187.facerec	2	174	25.3	2	174	25.3
188.amp	2	361	14.1	2	361	14.1
189.lucas	2	217	21.4	2	217	21.4
191.fma3d	2	274	17.8	2	274	17.8
200.sixtrack	2	243	10.5	2	243	10.5
301.apsi	2	337	17.9	2	337	17.9

Hardware

CPU: 64-bit Intel Xeon processor 3.6GHz, 2MB L2, 800MHz system bus
 CPU MHz: 3600
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12k micro-ops I + 16KBD on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x512 MB DDRII-RAM PC2-3200R
 Disk Subsystem: Fujitsu MAS3367NC (U320, 15krpm)
 Other Hardware: none

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
 Compiler: Intel C and Fortran Compiler 9.0 Build 20050722Z (for 32-bit applications), Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries), SmartHeap Library Version 7.4 from <http://www.microquill.com>
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Portability flags

178.galgel: -FI /F32000000

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO shlw32M.lib
 for C programs: -fast +FDO shlw32M.lib

Peak tuning flags

same as baseline (basepeak=true set globally)

New 32-bit Windows tools used, approved in May-2005

The system bus runs at 800 MHz



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX300 S2, 64-bit Intel Xeon 3.60 GHz

SPECfp_rate2000 = 22.1
SPECfp_rate_base2000 = 22.1

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>