



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM

IBM eServer 326m, 2.0 GHz Dual Core AMD Opteron(tm) Processor 270

SPECfp2000 = 1785

SPECfp\_base2000 = 1598

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2005 | Hardware Avail: Nov-2005 | Software Avail: Nov-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	72.4	2209	66.2	2416				
171.swim	3100	137	2256	129	2406				
172.mgrid	1800	136	1321	113	1591				
173.applu	2100	124	1693	111	1886				
177.mesa	1400	86.1	1626	81.3	1723				
178.galgel	2900	110	2627	97.5	2973				
179.art	2600	114	2283	85.0	3059				
183.earthquake	1300	91.3	1424	83.2	1563				
187.facerec	1900	91.2	2084	87.1	2182				
188.ammpp	2200	191	1152	170	1292				
189.lucas	2000	110	1825	98.7	2026				
191.fma3d	2100	164	1278	157	1338				
200.sixtrack	1100	188	585	156	705				
301.apsi	2600	186	1397	180	1444				

### Hardware

CPU: AMD Opteron(tm) Processor 270  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB (I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8 x 1024GB PC3200  
 Disk Subsystem: SCSI, 36GB 15K RPM  
 Other Hardware: None

### Software

Operating System: SuSE Linux 9.0 SP2 SLES 64 bit Kernel 2.6.5-7.191-smp (SP2)  
 Compiler: PathScale EKO Compiler Suite, Release 2.2.1  
 AMD Core Math Library 2.5.1  
 File System: Linux/reiserfs  
 System State: Multi-user, run level 3

## Notes/Tuning Information

Tested by IBM Corporation

+ACML: Linked with AMD Core Math Library

Base tuning for C programs: -Ofast -WOPT:mem\_opnds=on +FDO

Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast\_complex +FDO

Portability flags:

178.galgel: -fixedform

Peak tuning:

168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3

-OPT:unroll\_times\_max=8:unroll\_size=128:IEEE NaN\_Inf=off:ro=3

-IPA:linear=on:plimit=50000:callee\_limit=5000

-INLINE:aggressive=on

171.swim: -Ofast -CG:local\_fwd\_sched=on -LNO:fusion=2 -m3dnw

172.mgrid: -Ofast -CG:gcm=off:cflow=on -OPT:IEEE\_a=3:unroll\_size=200

-LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2

-WOPT:memopnds=on:aggstr=0

173.applu: -Ofast -CG:local\_fwd\_sched=on -OPT:ro=3 -TENV:X=3

-LNO:fusion=2:fission=2:full\_unroll\_size=10000:prefetch=3 +FDO

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM

IBM eServer 326m, 2.0 GHz Dual Core AMD Opteron(tm) Processor 270

SPECfp2000 = 1785

SPECfp\_base2000 = 1598

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2005 | Hardware Avail: Nov-2005 | Software Avail: Nov-2005

### Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel:    -Ofast -OPT:fast_complex +ACML +FDO
179.art:       -O3 -OPT:ofast -fno-math-errno -mno-sse2 -m32
183.earthquake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec:   -Ofast -LNO:fusion=2
               -OPT:fast_complex=on:IEEE_NaN_Inf=off:unroll_size=0 +FDO
188.amp:       -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
               -fno-math-errno -TENV:X=4 -LNO:prefetch=0 +FDO
189.lucas:     -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:memopnds=on +FDO
191.fma3d:     -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
               -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack:  -O3 -OPT:Ofast:Olimit=60000:early_intrinsics=on
               -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:      -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

BIOS Configuration Notes  
Node Interleaving is Disabled

Other Configuration Notes  
Taskset utility used to bind process to CPU(s)