



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY BX630, AMD Opteron (TM) 875

SPECint_rate2000 = 130
SPECint_rate_base2000 = 118

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Oct-2005 | Software Avail: Mar-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	120	108	8	120	108
175.vpr	8	135	96.0	8	132	98.8
176.gcc	8	73.9	138	8	73.9	138
181.mcf	8	275	60.6	8	224	74.7
186.crafty	8	70.4	132	8	64.1	145
197.parser	8	142	117	8	142	117
252.eon	8	76.7	157	8	55.0	219
253.perlbnk	8	131	127	8	119	141
254.gap	8	81.4	125	8	81.4	125
255.vortex	8	97.5	181	8	87.1	202
256.bzip2	8	147	94.8	8	144	96.6
300.twolf	8	222	126	8	171	163

Hardware

CPU: AMD Opteron (TM) 875 processor (2.20 GHz)
CPU MHz: 2200
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 64KBI + 64KBD on chip, per core
Secondary Cache: 1024KB (I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 16x1024MB DDR-RAM PC3200R
Disk Subsystem: Western Digital WD2500 (SATA, 7.2krpm)
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C++ 8.0
Build 20040318Z (for 32-bit applications),
Microsoft Visual Studio .Net 2003
7.1.3088 (for libraries),
SmartHeap Library Version 8.0
from <http://www.microquill.com>
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast -arch:SSE2 -Oi- +FDO
for C++ programs: -fast -GX -GR +FDO

Peak tuning flags

164.gzip: basepeak=yes
175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000,
-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO shlw32M.lib
181.mcf: -fast -QaxN +FDO shlw32M.lib
186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY BX630, AMD Opteron (TM) 875

SPECint_rate2000 = 130
SPECint_rate_base2000 = 118

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Oct-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

```
197.parser: basepeak=yes
252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
253.perlbnk: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes shlw32M.lib
254.gap: basepeak=yes
255.vortex: -fast -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
           -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
256.bzip2: -fast -Qunroll2 shlw32M.lib
300.twolf: -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

'start /b /wait /affinity' command is used to bind CPU(s) to processes

```
boot options: /NoExecute=alwaysoff
              /USEPMTIMER
BIOS settings: Memory Timing: 1T
              DRAM Bank Interleave=AUTO
```

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>