



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM Corporation

IBM eServer xSeries x306m (3.2GHz Pentium D 940, 2x2MB L2 Cache)

SPECfp\_rate2000 = 34.7

SPECfp\_rate\_base2000 = 34.0

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jan-2006 | Hardware Avail: Jan-2006 | Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	70.3	52.8	2	70.3	52.8
171.swim	2	228	31.6	2	228	31.5
172.mgrid	2	148	28.3	2	148	28.3
173.applu	2	179	27.3	2	176	27.8
177.mesa	2	99.9	32.5	2	99.9	32.5
178.galgel	2	93.8	71.7	2	93.8	71.7
179.art	2	80.2	75.3	2	80.2	75.3
183.quake	2	94.0	32.1	2	71.3	42.3
187.facerec	2	108	40.6	2	109	40.6
188.amp	2	190	26.8	2	190	26.8
189.lucas	2	150	30.8	2	151	30.6
191.fma3d	2	176	27.7	2	176	27.7
200.sixtrack	2	172	14.9	2	172	14.9
301.apsi	2	217	27.9	2	217	27.9

### Hardware

CPU: Intel Pentium D 940 (800 MHz system bus)  
CPU MHz: 3200  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 12K(I) micro-ops + 16KB(D) (on chip) per core  
Secondary Cache: 2048KB(I+D) (on chip) per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4 x 1024 MB ECC PC2-4200 Single Rank  
Disk Subsystem: 80GB SATA 10K RPM  
Other Hardware:

### Software

Operating System: Windows Server 2003 Standard Edition  
Compiler: Intel C/C++ Compiler 9.0 (20051130Z) for 32-bit applications  
Intel Fortran Compiler 9.0 (20051130Z) for 32-bit applications  
Microsoft Visual Studio .NET 13.0.9466 (for libraries)  
MicroQuill Smartheap Library 7.30  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

ONESTEP=yes  
+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### PORTABILITY

178.galgel: -FI /F32000000

### BASE TUNING

C/F77/F90: -fast -Qansi\_alias +FDO

### PEAK TUNING

168.wupwise: basepeak=yes  
171.swim: -fast -f77rtl +FDO  
172.mgrid: basepeak=yes  
173.applu: -fast -Qscalar\_rep- -Qauto -f77rtl +FDO  
177.mesa: -fast +FDO  
178.galgel: basepeak=yes  
179.art: basepeak=yes  
183.quake: -fast -Oa -Qrcd +FDO shlw32M.lib  
187.facerec: -fast -Qunroll1 -Qscalar\_rep- +FDO



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**IBM Corporation**

IBM eServer xSeries x306m (3.2GHz Pentium D 940, 2x2MB L2 Cache)

SPECfp\_rate2000 = 34.7

SPECfp\_rate\_base2000 = 34.0

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jan-2006 | Hardware Avail: Jan-2006 | Software Avail: Nov-2005

## Notes/Tuning Information (Continued)

188. ammp: basepeak=yes  
189. lucas: -fast  
191. fma3d: basepeak=yes  
200. sixtrack: -fast +FDO  
301. apsi: basepeak=yes