



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL45p (AMD Opteron (TM) 885)

SPECint\_rate2000 = 20.6  
SPECint\_rate\_base2000 = 19.6

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Mar-2006 Hardware Avail: Mar-2006 Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	98.1	16.6	1	98.1	16.6
175.vpr	1	103	15.8	1	99.4	16.3
176.gcc	1	58.5	21.8	1	57.9	22.1
181.mcf	1	164	12.8	1	137	15.3
186.crafty	1	59.0	19.7	1	53.7	21.6
197.parser	1	112	18.6	1	112	18.6
252.eon	1	50.1	30.1	1	45.6	33.1
253.perlbnk	1	103	20.2	1	103	20.2
254.gap	1	61.0	20.9	1	61.0	20.9
255.vortex	1	73.1	30.1	1	73.3	30.1
256.bzip2	1	111	15.6	1	110	15.8
300.twolf	1	175	19.9	1	144	24.2

### Hardware

CPU: AMD Opteron (TM) 885  
 CPU MHz: 2600  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2,4  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB(I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x2048MB PC3200 CL3.0  
 Disk Subsystem: 1x72.8GB 15K Ultra320 SCSI  
 Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise SP1  
 Compiler: Intel C++ Compiler 8.0 Build 20040318Z  
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
 MicroQuill Smartheap Library 7.0  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -GX -GR +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
 164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
 181.mcf: -fast -QaxN +FDO ONESTEP=yes
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
 197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
 252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 253.perlbnk: basepeak=yes
 254.gap: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL45p (AMD Opteron (TM) 885)

SPECint\_rate2000 = 20.6  
SPECint\_rate\_base2000 = 19.6

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Mar-2006 Hardware Avail: Mar-2006 Software Avail: Nov-2005

## Notes/Tuning Information (Continued)

```
255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
            -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO shlw32M.lib ONESTEP=yes
256.bzip2:  -fast -Qunroll2
300.twolf:  -fast -arch:SSE2 -Qansi_alias +FDO shlw32M.lib ONESTEP=yes
```

BIOS Configuration Notes  
Node Interleaving Disabled

Other Configuration Notes  
/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment.