



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries HS20 (2.0 GHz Xeon LV, 2MB L2 Shared Cache)

SPECfp_rate2000 = 30.9

SPECfp_rate_base2000 = 30.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Mar-2006 | Hardware Avail: Mar-2006 | Software Avail: Dec-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	153	48.4	4	153	48.4
171.swim	4	737	19.5	4	739	19.5
172.mgrid	4	487	17.2	4	487	17.2
173.applu	4	483	20.2	4	484	20.1
177.mesa	4	88.9	73.0	4	88.8	73.2
178.galgel	4	232	57.9	4	232	57.9
179.art	4	338	35.7	4	338	35.7
183.quake	4	265	22.7	4	202	29.9
187.facerec	4	213	41.4	4	212	41.6
188.amp	4	442	23.1	4	442	23.1
189.lucas	4	414	22.4	4	414	22.4
191.fma3d	4	372	26.2	4	372	26.2
200.sixtrack	4	222	22.9	4	222	23.0
301.apsi	4	318	37.9	4	318	37.9

Hardware

CPU: Dual-Core Intel Processor Xeon LV 2.0GHz (667 MHz system bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) (on chip) per core
Secondary Cache: 2048KB(I+D) (on chip) shared by 2 cores
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 2048 MB ECC PC2-3200 Single Rank
Disk Subsystem: 73GB SCSI 10K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
Compiler: Intel C/C++ Compiler 9.0 (20051130Z) for 32-bit applications
Intel Fortran Compiler 9.0 (20051120Z) for 32-bit applications
Microsoft Visual Studio .NET 13.0.9466 (for libraries)
MicroQuill Smartheap Library 7.30
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY

178.galgel: -FI /F32000000

BASE TUNING

C/F77/F90: -fast -Qansi_alias +FDO

PEAK TUNING

168.wupwise: basepeak=yes
171.swim: -fast -f77rtl +FDO
172.mgrid: basepeak=yes
173.applu: -fast -Qscalar_rep- -Qauto -f77rtl +FDO
177.mesa: -fast +FDO
178.galgel: basepeak=yes
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd +FDO shlw32M.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries HS20 (2.0 GHz Xeon LV, 2MB L2 Shared Cache)

SPECfp_rate2000 = 30.9

SPECfp_rate_base2000 = 30.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Mar-2006 | Hardware Avail: Mar-2006 | Software Avail: Dec-2005

Notes/Tuning Information (Continued)

188.amm: basepeak=yes
189.lucas: -fast
191.fma3d: basepeak=yes
200.sixtrack: -Qipo +FDO
301.apsi: basepeak=yes