



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX100 S3, Intel Pentium D 950 processor, 3.40 GHz

SPECfp_rate2000 = 39.0

SPECfp_rate_base2000 = 39.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Apr-2006 | Hardware Avail: Jun-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	58.8	63.1	2	58.8	63.1
171.swim	2	217	33.1	2	217	33.1
172.mgrid	2	137	30.4	2	137	30.4
173.applu	2	165	29.5	2	165	29.5
177.mesa	2	78.5	41.4	2	78.5	41.4
178.galgel	2	87.4	77.0	2	87.4	77.0
179.art	2	51.6	117	2	51.6	117
183.quake	2	80.5	37.4	2	80.5	37.4
187.facerec	2	99.2	44.4	2	99.2	44.4
188.amp	2	162	31.6	2	162	31.6
189.lucas	2	143	32.5	2	143	32.5
191.fma3d	2	151	32.2	2	151	32.2
200.sixtrack	2	162	15.7	2	162	15.7
301.apsi	2	192	31.5	2	192	31.5

Hardware

CPU: Intel Pentium D 950 processor (3.40 GHz, 2x2MB L2, 800 MHz system bus)
CPU MHz: 3400
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x2GB DDRII-RAM PC2-4200E (CAS 4-4-4)
Disk Subsystem: Seagate ST380013AS (SATA, 7.2krpm, 80GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext3
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX100 S3, Intel Pentium D 950 processor, 3.40 GHz

SPECfp_rate2000 = 39.0

SPECfp_rate_base2000 = 39.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Apr-2006 | Hardware Avail: Jun-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 800 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>