



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant ML370 G5 (3.0GHz, Intel Xeon processor 5160)

SPECfp\_rate2000 = 46.3

SPECfp\_rate\_base2000 = 45.4

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: May-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	55.0	67.5	2	55.0	67.5
171.swim	2	223	32.3	2	222	32.4
172.mgrid	2	163	25.5	2	164	25.5
173.applu	2	148	33.0	2	148	33.0
177.mesa	2	51.4	63.2	2	49.4	65.7
178.galgel	2	53.1	127	2	53.1	127
179.art	2	51.3	118	2	51.3	118
183.quake	2	63.6	47.4	2	63.6	47.4
187.facerec	2	82.6	53.3	2	83.5	52.8
188.amp	2	149	34.3	2	117	43.7
189.lucas	2	142	32.7	2	141	32.9
191.fma3d	2	142	34.3	2	142	34.3
200.sixtrack	2	93.3	27.4	2	93.3	27.3
301.apsi	2	175	34.4	2	175	34.4

### Hardware

CPU: Intel Xeon processor 5160 (3.0GHz, 4MB L2 shared, 1333MHz bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32KB (I) + 32KB (D) (on chip) per core  
Secondary Cache: 4096KB(I+D) (on chip) shared  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x2048MB PC2-5300F  
Disk Subsystem: 1x36GB SAS  
Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise SP1  
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)  
Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
MicroQuill Smartheap Library 7.0  
File System: NTFS  
System State: Default

## Notes/Tuning Information

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

Base tuning for Fortran programs: -fast -Qansi\_alias +FDO

Base tuning for C programs: -fast +FDO shlw32M.lib

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -fast -Qansi\_alias +FDO

171.swim: -fast +FDO ONESTEP=yes

172.mgrid: -fast -Qansi\_alias +FDO

173.applu: basepeak=1

177.mesa: -fast +FDO ONESTEP=yes

178.galgel: basepeak=1

179.art: basepeak=1 +FDO ONESTEP=yes shlw32M.lib

183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes

187.facerec: -fast -Qunroll1 -Qscalar\_rep- +FDO ONESTEP=yes



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant ML370 G5 (3.0GHz, Intel Xeon processor 5160)

SPECfp\_rate2000 = 46.3  
SPECfp\_rate\_base2000 = 45.4

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: May-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

188. ammp: -fast -Qansi\_alias +FDO  
189. lucas: -fast  
191. fma3d: basepeak=1  
200. sixtrack: -fast +FDO  
301. apsi: basepeak=1