



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell
PowerEdge 1955 (Intel Xeon processor 5130, 2.00GHz)

SPECint2000 = 2120
SPECint_base2000 = 2116

SPEC license #: 55 Tested by: Dell, Round Rock, TX Test date: Jun-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	113	1240	113	1239	
175.vpr	1400	89.9	1557	88.2	1588	
176.gcc	1100	45.4	2423	45.4	2423	
181.mcf	1800	54.8	3287	54.8	3287	
186.crafty	1000	54.8	1824	54.9	1821	
197.parser	1800	108	1667	108	1672	
252.eon	1300	49.7	2616	49.7	2615	
253.perlbmk	1800	73.3	2455	73.3	2455	
254.gap	1100	52.7	2089	52.4	2099	
255.vortex	1900	53.2	3570	53.2	3570	
256.bzip2	1500	95.9	1564	96.1	1561	
300.twolf	3000	130	2305	130	2305	

Hardware

CPU: Intel Xeon processor 5130 (1333MHz system bus)
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4096KB(I+D) on chip, shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1GB 667MHz ECC CL5 DDR2 FB-DIMM
 Disk Subsystem: 1 x 73GB SAS 10000 RPM
 Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
 Compiler: Intel C++ Compiler 9.1 for IA32(20060323Z)
 Microsoft Visual Studio .NET 2003(7.1.3088)
 MicroQuill SmartHeap Library 8.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast +FDO shlw32m.lib
 C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
 175.vpr: -fast +FDO
 176.gcc: basepeak=yes
 181.mcf: basepeak=yes
 186.crafty: -fast -Oa +FDO shlw32m.lib
 197.parser: -fast +FDO
 252.eon: -fast +FDO
 253.perlbmk: basepeak=yes



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1955 (Intel Xeon processor 5130, 2.00GHz)

SPECint2000 = 2120

SPECint_base2000 = 2116

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

254.gap: -fast +FDO
255.vortex basepeak=yes
256.bzip2: -fast -Qunroll11 -Oa +FDO
300.twolf: basepeak=yes