



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell
PowerEdge 1955 (Intel Xeon processor 5160, 3.00GHz)

SPECint2000 = **3016**
SPECint_base2000 = **3010**

SPEC license #: 55 Tested by: Dell, Round Rock, TX Test date: Jun-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	75.9	1844	76.0	1842	
175.vpr	1400	64.3	2177	63.1	2219	
176.gcc	1100	35.5	3094	35.5	3094	
181.mcf	1800	43.3	4154	43.3	4154	
186.crafty	1000	36.6	2734	36.6	2731	
197.parser	1800	73.5	2448	73.3	2456	
252.eon	1300	33.2	3919	33.2	3919	
253.perlbmk	1800	49.4	3641	49.4	3641	
254.gap	1100	37.9	2906	37.7	2920	
255.vortex	1900	38.3	4963	38.3	4963	
256.bzip2	1500	66.5	2255	66.7	2250	
300.twolf	3000	86.8	3458	86.8	3458	

Hardware

CPU: Intel Xeon processor 5160 (1333MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1GB 667MHz ECC CL5 DDR2 FB-DIMM
Disk Subsystem: 1 x 73GB SAS 10000 RPM
Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ Compiler 9.1 for IA32(20060323Z)
Microsoft Visual Studio .NET 2003(7.1.3088)
MicroQuill SmartHeap Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast +FDO shlw32m.lib
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Oa +FDO shlw32m.lib
197.parser: -fast +FDO
252.eon: -fast +FDO
253.perlbmk: basepeak=yes



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1955 (Intel Xeon processor 5160, 3.00GHz)

SPECint2000 = 3016

SPECint_base2000 = 3010

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Jun-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

254.gap: -fast +FDO
255.vortex basepeak=yes
256.bzip2: -fast -Qunroll11 -Oa +FDO
300.twolf: basepeak=yes