



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G5 (1.6 GHz, Intel Xeon processor 5110)

SPECint2000 = 1710
SPECint_base2000 = 1704

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	141	996	141	995	
175.vpr	1400	112	1248	108	1298	
176.gcc	1100	56.4	1950	56.4	1950	
181.mcf	1800	65.0	2768	65.0	2769	
186.crafty	1000	68.1	1468	68.2	1467	
197.parser	1800	134	1340	134	1346	
252.eon	1300	62.1	2093	62.3	2086	
253.perlbmk	1800	92.5	1946	92.3	1951	
254.gap	1100	65.9	1670	65.8	1673	
255.vortex	1900	65.6	2896	65.6	2895	
256.bzip2	1500	119	1260	119	1260	
300.twolf	3000	164	1830	164	1830	

Hardware

CPU: Intel Xeon processor 5110 (1.6 GHz, 4 MB L2 shared, 1066 MHz bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip shared
L3 Cache: N/A
Other Cache: N/A
Memory: 16 GB (8x2048 MB PC2-5300F)
Disk Subsystem: 1x36 GB 10 K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib

Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbmk: -DSPEC_CPU2000_NTOS -DPERL DLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -fast +FDO ONESTEP=yes

175.vpr: -fast +FDO ONESTEP=yes

176.gcc: basepeak=1

181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib

186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

197.parser: -fast +FDO ONESTEP=yes

252.eon: -fast +FDO

253.perlbmk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib

254.gap: -fast +FDO ONESTEP=yes

255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G5 (1.6 GHz, Intel Xeon processor 5110)

SPECint2000 = 1710
SPECint_base2000 = 1704

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Notes/Tuning Information (Continued)

256.bzip2: basepeak=1
300.twolf: -fast +FDO shlw32M.lib
BIOS Configuration Notes
Power Regulator set to Static High Performance Mode