



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(2.67 GHz, Intel(R) Core(TM) 2 processor E6700)

SPECfp2000 = 2850

SPECfp_base2000 = 2847

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	35.6	4489	35.7	4487	
171.swim	3100	93.4	3319	93.4	3318	
172.mgrid	1800	102	1764	102	1764	
173.applu	2100	89.7	2342	89.7	2342	
177.mesa	1400	55.5	2523	55.5	2523	
178.galgel	2900	44.9	6465	44.9	6465	
179.art	2600	27.8	9348	27.8	9348	
183.quake	1300	35.0	3714	34.3	3789	
187.facerec	1900	66.0	2877	66.2	2872	
188.amp	2200	113	1953	112	1968	
189.lucas	2000	69.9	2860	69.9	2860	
191.fma3d	2100	101	2089	101	2089	
200.sixtrack	1100	103	1067	104	1054	
301.apsi	2600	141	1844	141	1844	

Hardware

CPU: Intel(R) Core(TM) 2 processor E6700(2.67 GHz, 1066 MHz bus)
CPU MHz: 2667
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32KBI + 32KBD per core
Secondary Cache: 4MB(I+D) shared, per chip
L3 Cache: None
Other Cache: None
Memory: 2 GB (2 1GB Corsair TWIN2X2048-8500C5 DDR2 1066 CL5-5-5 DIMMs)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: ATI Radeon X1900 XTX PCI express graphics card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_FC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO shlW32M.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlW32M.lib
189.lucas: -fast -Qprefetch- +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(2.67 GHz, Intel(R) Core(TM) 2 processor E6700)

SPECfp2000 = 2850

SPECfp_base2000 = 2847

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 07/2006

<http://www.intel.com/products/motherboard/dg965wh/index.htm>

The system bus runs at 1066 MHz