



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Intel(R) Corporation

Intel(R) DG965WH motherboard( 2.93 GHz, Intel(R) Core(TM) 2 Extreme processor X6800)

SPECint2000 = 3111

SPECint\_base2000 = 3106

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	76.8	1822	76.6	1828	
175.vpr	1400	61.7	2270	60.2	2324	
176.gcc	1100	32.5	3385	32.5	3385	
181.mcf	1800	35.6	5050	35.6	5050	
186.crafty	1000	36.7	2723	36.8	2714	
197.parser	1800	78.4	2297	78.5	2293	
252.eon	1300	34.0	3820	34.0	3825	
253.perlbmk	1800	49.4	3643	49.5	3634	
254.gap	1100	35.7	3078	35.7	3078	
255.vortex	1900	35.5	5352	35.5	5352	
256.bzip2	1500	63.4	2366	63.6	2360	
300.twolf	3000	89.2	3363	89.2	3362	

### Hardware

CPU: Intel(R) Core(TM) 2 Extreme processor X6800( 2.93 GHz, 1066 MHz bus)  
CPU MHz: 2933  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 32KBI + 32KBD per core, on chip  
Secondary Cache: 4MB(I+D) shared, per chip, on chip  
L3 Cache: None  
Other Cache: None  
Memory: 2 GB (2 1GB Corsair TWIN2X2048-8500C5 DDR2 1066 CL5-5-5 DIMMs)  
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)  
Other Hardware: ATI Radeon X1900 XTX PCI express graphics card

### Software

Operating System: Windows XP Professional SP2  
Compiler: Intel C++ Compiler 9.1 for 32-bit applications  
Build 20060323Z Package ID: W\_CC\_P\_9.1.020  
Microsoft Visual Studio 2005(for libraries)  
SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlw32M-80.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard( 2.93 GHz, Intel(R) Core(TM) 2 Extreme processor X6800)

SPECint2000 = 3111

SPECint\_base2000 = 3106

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO

300.twolf: -fast -O3 +FDO shlw32M-80.lib

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 07/2006

<http://www.intel.com/products/motherboard/dg965wh/index.htm>

The system bus runs at 1066 MHz