



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System p5 550Q (1650 MHz, 1 CPU)

SPECfp2000 = 2612  
SPECfp\_base2000 = 2458

SPEC license #: 11 | Tested by: IBM Austin | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	67.8	2360	57.2	2799
171.swim	3100	96.9	3201	96.9	3201
172.mgrid	1800	81.7	2202	78.0	2309
173.applu	2100	104	2014	98.4	2134
177.mesa	1400	117	1198	116	1205
178.galgel	2900	53.3	5439	40.0	7241
179.art	2600	19.3	13493	18.9	13760
183.quake	1300	25.8	5036	25.4	5121
187.facerec	1900	84.8	2240	83.3	2280
188.amp	2200	177	1240	161	1371
189.lucas	2000	44.0	4543	40.1	4992
191.fma3d	2100	148	1417	143	1466
200.sixtrack	1100	152	724	152	726
301.apsi	2600	170	1527	171	1525

### Hardware

CPU: POWER5+  
 CPU MHz: 1650  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (SMT off)  
 CPU(s) orderable: 4,8 cores  
 Parallel: No  
 Primary Cache: 64 KB I + 32 KB D on chip per core  
 Secondary Cache: 1920 KB I+D on chip per chip  
 L3 Cache: 36 MB I+D off chip per chip  
 Other Cache: None  
 Memory: 64 GB (16x4 GB)  
 Disk Subsystem: 1x73GB SCSI, 15K RPM  
 Other Hardware: None

### Software

Operating System: AIX 5L V5.3  
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX  
 XL Fortran Enterprise Edition Version 10.1 for AIX  
 Other Software: ESSL 4.2.0.4  
 File System: AIX/JFS2  
 System State: Multi-user

## Notes/Tuning Information

### Portability Flags:

-qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu,  
 178.galgel, 200.sixtrack, 301.apsi  
 -qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

### Base Optimization Flags:

Fortran: -O5 -lhmu -blpdata -lmass  
 C: -qpdf1/pdf2  
 -O5 -blpdata -qalign=natural

### Peak Optimization Flags

168.wupwise: -O5 -qsave -blpdata -lhmu -lmass  
 171.swim: basepeak=1  
 172.mgrid: -qpdf1/pdf2  
 -O4 -qipa=partition=large -q64 -blpdata  
 173.applu: -O5 -qarch=pwr3 -qtune=pwr3 -qalign=struct=natural -qfdpr -q64 -blpdata  
 fdpr -q -O3



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 550Q (1650 MHz, 1 CPU)

SPECfp2000 = 2612

SPECfp\_base2000 = 2458

SPEC license #: 11 | Tested by: IBM Austin | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

## Notes/Tuning Information (Continued)

```

177.mesa:      -qpdf1/pdf2
                -O5 -qfdpr
                fdpr -q -O3
178.galgel:    -qpdf1/pdf2
                -O5 -qfdpr -lhmu -blpdata -lmass -qessl -lessl
                fdpr -q -O3
179.art:       -qpdf1/pdf2
                -O5 -qhot=arraypad -Q -qalign=natural -blpdata -lhmu
183.earthquake: -qpdf1/pdf2
                -O3 -qarch=auto -qtune=auto -qipa=level=2 -blpdata
187.facerec:   -O5 -qsave -blpdata
188.ammp:      -O5 -qalign=natural -qfdpr -blpdata -lhmu
                fdpr -q -O3
189.lucas:     -O3 -qarch=auto -qtune=auto -qfdpr -blpdata -qessl -lessl
                fdpr -q -O3
191.fma3d:     -qpdf1/pdf2
                -O3 -qarch=auto -qtune=auto -qipa=level=2 -q64 -lhmu -blpdata -lmass
200.sixtrack:  -qpdf1/pdf2
                -O4 -qfdpr
                fdpr -q -O3
301.apsi:      -O5

```

The installed OS level is AIX 5L for POWER Version 5.3 with the 5300-05 Recommended Technology Level.  
 The installed C/C++ compiler is XL C/C++ Enterprise Edition Version 8.0 for AIX with the March 2006 PTF.  
 The installed Fortran compiler is XL Fortran Enterprise Edition Version 10.1 with the May 2006 AIX PTF.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

SUT: Acronym for "System Under Test"

ESSL: Engineering and Scientific Subroutine Library

PTF: IBM identifier for "Program Fix Level"

```

ANSI C89:      IBM XL C for AIX invoked as xlc
Fortran 77:    IBM XL Fortran for AIX invoked as xlf90
Fortran 90:    IBM XL Fortran for AIX invoked as xlf90

```

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=128 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
bosboot -aD
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \${\$} \${SPECUSERNUM}; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.

Seven cores were deconfigured and SMT disabled using the AIX commands

```

smtctl -m off -w boot
bosboot -aD
shutdown -rF
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu

```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 550Q (1650 MHz, 1 CPU)

SPECfp2000 = 2612

SPECfp\_base2000 = 2458

SPEC license #: 11 | Tested by: IBM Austin | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

## Notes/Tuning Information (Continued)

```
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu
drmgr -r -c cpu
```