



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E25K (72 processor)

SPECint_rate2000 = 1644
SPECint_rate_base2000 = 1413

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jun-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	144	204	1144	144	186	1254
175.vpr	144	178	1316	144	170	1378
176.gcc	144	222	829	432	326	1693
181.mcf	144	254	1181	432	641	1407
186.crafty	144	83.3	2006	144	77.3	2161
197.parser	144	220	1370	144	186	1615
252.eon	144	105	2076	144	99.0	2193
253.perlbnk	144	180	1670	144	174	1732
254.gap	144	280	656	144	208	883
255.vortex	144	118	2693	144	113	2819
256.bzip2	144	164	1531	144	160	1562
300.twolf	144	300	1671	144	272	1845

Hardware

CPU: UltraSPARC IV+
CPU MHz: 1800
FPU: Integrated
CPU(s) enabled: 144 cores, 72 chips, 2 cores/chip
CPU(s) orderable: 4-72 (order by number of chips, groups of 4)
Parallel: No
Primary Cache: 64KBI+64KBD per core on chip
Secondary Cache: 2MB(I+D) per chip (on chip)
L3 Cache: 32MB(I+D) per chip (off chip)
Other Cache: None
Memory: 288GB 16-way interleaved (576x512MB)
Disk Subsystem: Sun StorageTek S1 Disk Array (2x73GB, 10000 RPM)
Sun StorageTek 6130 Array (14x73GB, 10000 RPM)
Other Hardware: None

Software

Operating System: Solaris 10 6/06
Compiler: Sun Studio 11
File System: ufs
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes for all benchmarks
Profile feedback used for those marked with +FDO

164.zip: -x04 -xbuiltin=%all -xtarget=native -xalias_level=std
-xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=30,
-Qeps:do_spec_load=1 +FDO
175.vpr: -fast -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1,
-Qeps:rp_filtering_margin=30 -xipo=2 -xpagesize_stack=8K
-lmopt -lm +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E25K (72 processor)

SPECint_rate2000 = 1644
SPECint_rate_base2000 = 1413

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jun-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

Notes/Tuning Information (Continued)

```

176.gcc: -fast -xipo=2 -Wc,-Qicache-chbab=1 -Wc,-Qeps:enabled=1
        -Qeps:ws=32 -Wc,-Qdepgraph-early_cross_call=1
        -Wc,-Qms_pipe-pref_prolog -l12amm +FDO
181.mcf: -fast -xipo=2 -xprefetch_level=2
186.crafty: -fast -xpagesize=8k -xipo=2 -xalias_level=strong
        -W2,-Ashort_ldst -xinline= -xprefetch -xrestrict
        +FDO (-xlinkopt during pass2)
197.parser: -fast -xipo=2 -xalias_level=strong -Wc,Qgsched-T6
        -Wc,-Qipa:valueprediction -Wc,-Qms_pipe-prefstrong=0,
        -Qlp-pt=weak +FDO
252.eon: -fast -xipo=2 -xalias_level=compatible -Qoption cg
        -Qeps:enabled=1 -xvector -Qoption iropt -Abcopy -xunroll=16
        +FDO
253.perlbnk: -fast -xipo -Wc,-Qeps:enabled=1,-Qeps:ws=16 -xalias_level=std
        -xsafe=mem -Wc,-Qiselect-funcalign=128,-Qicache-chbab=1
        -Wc,-Qiselect-sw_pf_tbl_th=40,-Qeps:do_spec_load=1 +FDO
254.gap: -fast -W2,-Abcopy -xvector -xprefetch_level=3 +FDO
255.vortex: -fast -xrestrict -xipo=2 -Wc,-Qeps:enabled=1
        -W2,-Ainline:recursion=1:cs=400:irs=5000
        -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=64
        -Wc,-Qpeep-Sh0 -W2,-crit -xprefetch=latx:1.7 -fsimple=1
        -Wc,-Qiselect-sw_pf_tbl_th=30 -Wc,-Qicache-chbab=1
        -W2,-Ainline:inc=300 -l12amm +FDO
256.bzip2: -fast -xipo=2 -xalias_level=strong -xrestrict
        -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1 +FDO
300.twolf: -fast -xalias_level=strong -xsafe=mem -xipo=2
        -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp -xinline= +FDO

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback

```

Portability:

```

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
        -DSYS_HAS_CALLOC_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

For 254.gap peak, jobs were bound to cores using the pbind command.

The system was configured with multiple file systems.
The O/S was installed on one disk of the Sun StorageTek S1 Disk
Array (ufs, ufs w/logging). The benchmark was run on the Sun
StorageTek 6130 Array, using H/W Raid 5 and ufs with ufs logging



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E25K (72 processor)

SPECint_rate2000 = 1644

SPECint_rate_base2000 = 1413

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jun-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

Notes/Tuning Information (Continued)

file system.