



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS R640, Intel Xeon 5130 processor

SPECint2000 = 2126
SPECint_base2000 = 2119

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: Aug-2006 Hardware Avail: Aug-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	113	1244	113	1243	
175.vpr	1400	89.4	1566	88.0	1590	
176.gcc	1100	45.6	2412	45.6	2412	
181.mcf	1800	55.6	3236	55.6	3236	
186.crafty	1000	54.9	1822	54.3	1843	
197.parser	1800	108	1662	108	1668	
252.eon	1300	49.8	2613	49.8	2613	
253.perlbmk	1800	72.4	2487	72.4	2486	
254.gap	1100	52.4	2098	51.5	2136	
255.vortex	1900	53.4	3557	53.4	3557	
256.bzip2	1500	93.2	1610	93.4	1606	
300.twolf	3000	132	2274	132	2274	

Hardware

CPU: Intel Xeon 5130 processor (2.0 GHz, 1333 MHz system bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KBI + 32KBD on chip, per core
Secondary Cache: 4096KB(I+D) on chip, per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 GB (8x1 GB DDRII 5300F, 2rank, CL5-5-5, with ECC)
Disk Subsystem: Serial ATA 7200 rpm
Other Hardware:

Software

Operating System: Windows XP, 64 bit Edition
Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.1,
- Build 20060519Z Package ID: W_CC_P_9.1.025
Microsoft Visual Studio .NET 2003 (for libraries)
MicroQuill SmartHeap Library, Version 8 (shlW32M.lib)
File System: NTFS
System State: Default

Notes/Tuning Information

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Feedback optimization:

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:

for C programs:
-fast +FDO shlW32M.lib
for C++ program 252.eon:
-fast -Qcxx_features +FDO

Peak Tuning Flags:

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: -fast +FDO shlW32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
CELSIUS R640, Intel Xeon 5130 processor

SPECint2000 =	2126
SPECint_base2000 =	2119

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
186.crafty: -fast +FDO
197.parser: -fast +FDO
252.eon: -fast -Qcxx_features +FDO
253.perlbnk: -fast +FDO shlw32M.lib
254.gap: -fast +FDO
255.vortex -fast +FDO shlw32M.lib
256.bzip2: -fast +FDO
300.twolf: -fast +FDO shlw32M.lib
```

Extra Libraries:

shlw32M.lib = Microquill SmartHeap Library 8
see www.microquill.com

Compilation was done in
Windows XP Professional, Service Pack 2

Snoop Filter was enabled in BIOS

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>