



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM Corporation

AMD Opteron LS41 for IBM BladeCenter (AMD Opteron (TM) 8212)

SPECfp2000 = 1659

SPECfp\_base2000 = 1521

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	77.1	2074	69.5	2304				
171.swim	3100	139	2236	129	2406				
172.mgrid	1800	131	1379	118	1526				
173.applu	2100	132	1587	119	1770				
177.mesa	1400	90.7	1544	84.9	1649				
178.galgel	2900	115	2526	115	2532				
179.art	2600	138	1884	102	2557				
183.quake	1300	110	1177	100	1294				
187.facerec	1900	97.6	1946	94.8	2003				
188.amp	2200	192	1144	184	1195				
189.lucas	2000	118	1701	99.0	2020				
191.fma3d	2100	163	1289	166	1268				
200.sixtrack	1100	168	656	158	698				
301.apsi	2600	206	1261	193	1350				

### Hardware

CPU: AMD Opteron 8212  
CPU MHz: 2000  
FPU: Integrated  
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip  
CPU(s) orderable: 1,2,3,4  
Parallel: No  
Primary Cache: 64KBI + 64KBD (on chip) per core  
Secondary Cache: 1024KB (I+D) (on chip) per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 16x2GB, PC2-5300  
Disk Subsystem: SAS, 36GB 10K RPM  
Other Hardware: None

### Software

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp  
Compiler: PathScale EKO Compiler Suite, Release 2.4  
PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
File System: Linux/reiserfs  
System State: Multi-user, run level 3

## Notes/Tuning Information

+FDO: PASS1= -fb\_create fbdata PASS2= -fb\_opt fbdata

### Baseline optimization

C programs: -Ofast -WOPT:mem\_opnds=on +FDO  
Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast\_complex=on +FDO  
Portability Flags:  
178.galgel: -fixedform

### Peak Tuning:

168.wupwise: -Ofast -IPA:linear=on -LNO:prefetch Ahead=5:prefetch=3  
-OPT:unroll\_times\_max=8:unroll\_size=128:IEEE\_NaN\_Inf=off:ro=3  
171.swim: -Ofast -CG:local\_fwd\_sched=on -LNO:fusion=2 -m3dnow  
172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE\_arith=3:unroll\_size=200  
-LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2  
-WOPT:mem\_opnds=on:aggstr=0  
173.applu: -Ofast -CG:local\_fwd\_sched=on -OPT:ro=3 -TENV:X=3  
-LNO:fusion=2:fission=2:full\_unroll\_size=10000 +FDO



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**IBM Corporation**

AMD Opteron LS41 for IBM BladeCenter (AMD Opteron (TM) 8212)

SPECfp2000 = 1659

SPECfp\_base2000 = 1521

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Mar-2006

## Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel:    -Ofast -OPT:fast_complex=on +FDO
179.art:       -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.quake:    -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec:  -Ofast -IPA:plimit=1500 -LNO:fusion=2
              -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 +FDO
188.amp:      -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
              -GRA:optimize_boundary=on -fno-math-errno -TENV:X=4 +FDO
189.lucas:    -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d:    -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
              -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:early_intrinsics=on
              -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:     -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```