



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(1.86 GHz, Intel(R) Core(TM) 2 processor E6300)

SPECint_rate2000 = 38.7

SPECint_rate_base2000 = 38.7

SPEC license #: 13 Tested by: Intel(R) Corporation Test date: Jul-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	124	26.2	2	123	26.4
175.vpr	2	132	24.7	2	128	25.3
176.gcc	2	57.8	44.2	2	57.8	44.2
181.mcf	2	149	28.1	2	149	28.1
186.crafty	2	59.4	39.1	2	59.6	39.0
197.parser	2	138	30.2	2	138	30.2
252.eon	2	53.8	56.1	2	53.6	56.2
253.perlbnk	2	81.2	51.4	2	81.6	51.2
254.gap	2	57.5	44.4	2	57.5	44.4
255.vortex	2	62.2	70.8	2	62.2	70.8
256.bzip2	2	127	27.5	2	127	27.3
300.twolf	2	147	47.3	2	147	47.5

Hardware

CPU: Intel(R) Core(TM) 2 processor E6300(1.86 GHz, 1066 MHz bus)
CPU MHz: 1867
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32KBI + 32KBD per core, on chip
Secondary Cache: 2MB(I+D) shared, per chip, on chip
L3 Cache: None
Other Cache: None
Memory: 2 GB (2 1GB Corsair TWIN2X2048-8500C5 DDR2 1066 CL5-5-5 DIMMs)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: ATI Radeon X850 XT PCI express graphics card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_CC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M-80.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M-80.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M-80.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(1.86 GHz, Intel(R) Core(TM) 2 processor E6300)

SPECint_rate2000 = 38.7

SPECint_rate_base2000 = 38.7

SPEC license #: 13 | Tested by: Intel(R) Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO

300.twolf: -fast -O3 +FDO shlw32M-80.lib

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 07/2006

<http://www.intel.com/products/motherboard/dg965wh/index.htm>

The system bus runs at 1066 MHz