



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M, 3.20 GHz

SPECfp_rate2000 = 66.4

SPECfp_rate_base2000 = 66.4

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Feb-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	148	100	8	148	100
171.swim	8	554	51.9	8	554	51.9
172.mgrid	8	348	48.0	8	348	48.0
173.applu	8	396	49.2	8	396	49.2
177.mesa	8	178	73.2	8	178	73.2
178.galgel	8	180	149	8	180	149
179.art	8	136	177	8	136	177
183.quake	8	240	50.4	8	240	50.4
187.facerec	8	234	75.5	8	234	75.5
188.amp	8	353	57.8	8	353	57.8
189.lucas	8	367	50.6	8	367	50.6
191.fma3d	8	361	53.9	8	361	53.9
200.sixtrack	8	276	36.9	8	276	36.9
301.apsi	8	397	60.8	8	397	60.8

Hardware

CPU: Intel Xeon processor 7130M (3.20 GHz, 2x1MB L2, 8MB L3, 800 MHz system bus)
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)
 CPU(s) orderable: 1,2,4 chips
 Parallel: No
 Primary Cache: 12k micro-ops(I) + 16KB(D) on chip, per core
 Secondary Cache: 1024KB(I+D) on chip, per core
 L3 Cache: 8MB on chip, per chip
 Other Cache: N/A
 Memory: 16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)
 Disk Subsystem: Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)
 Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
 Kernel 2.6.5-7.244-smp on an x86_64
 Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
 Build 20060120 (for 64-bit applications)
 File System: ext3
 System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
 PASS1: -prof_gen PASS2: -prof_use

Optimization flags
 ONESTEP=yes set for all benchmarks

Portability flags
 -DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran

Base tuning flags
 for Fortran and C programs: -fast +FDO

Peak tuning flags
 same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7130M, 3.20 GHz

SPECfp_rate2000 = 66.4

SPECfp_rate_base2000 = 66.4

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Feb-2006

Notes/Tuning Information (Continued)

The system bus runs at 800 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>