



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX600 S3, Intel Xeon processor 7140M, 3.40 GHz

SPECint\_rate2000 = 43.0

SPECint\_rate\_base2000 = 43.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	190	34.2	4	190	34.2
175.vpr	4	226	28.7	4	226	28.7
176.gcc	4	95.6	53.4	4	95.6	53.4
181.mcf	4	159	52.4	4	159	52.4
186.crafty	4	157	29.6	4	157	29.6
197.parser	4	204	41.0	4	204	41.0
252.eon	4	104	57.8	4	104	57.8
253.perlbnk	4	186	44.8	4	186	44.8
254.gap	4	123	41.4	4	123	41.4
255.vortex	4	132	66.5	4	132	66.5
256.bzip2	4	173	40.3	4	173	40.3
300.twolf	4	332	41.9	4	332	41.9

### Hardware

CPU: Intel Xeon processor 7140M (3.40 GHz, 2x1MB L2, 16MB L3, 800 MHz system bus)  
CPU MHz: 3400  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1,2,4 chips  
Parallel: No  
Primary Cache: 12k micro-ops(I) + 16KB(D) on chip, per core  
Secondary Cache: 1024KB(I+D) on chip, per core  
L3 Cache: 16MB on chip, per chip  
Other Cache: N/A  
Memory: 16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)  
Disk Subsystem: Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)  
Other Hardware: none

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)  
Compiler: Intel C++ Compiler 9.1  
Build 20060323Z (for 32-bit applications),  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries),  
SmartHeap Library Version 8.0  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### Portability flags

176.gcc: -Dalloca=\_alloca /F10000000  
186.crafty: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### Base tuning flags

for C programs: -fast +FDO shlw32m.lib  
for C++ programs: -fast -Qcxx\_features +FDO shlw32m.lib

### Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX600 S3, Intel Xeon processor 7140M, 3.40 GHz

SPECint\_rate2000 = 43.0

SPECint\_rate\_base2000 = 43.0

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

This result was measured on the PRIMERGY TX600 S3. The PRIMERGY TX600 S3 and the PRIMERGY RX600 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>