



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System X 3105 (AMD Opteron (TM) 1210)

SPECfp2000 = 1678
SPECfp_base2000 = 1546

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	75.6	2116	67.1	2384	[Bar chart showing ratio bars for 168.wupwise]			
171.swim	3100	136	2275	127	2434	[Bar chart showing ratio bars for 171.swim]			
172.mgrid	1800	137	1318	119	1507	[Bar chart showing ratio bars for 172.mgrid]			
173.applu	2100	127	1657	118	1784	[Bar chart showing ratio bars for 173.applu]			
177.mesa	1400	97.1	1442	90.8	1541	[Bar chart showing ratio bars for 177.mesa]			
178.galgel	2900	117	2488	116	2499	[Bar chart showing ratio bars for 178.galgel]			
179.art	2600	116	2235	89.1	2918	[Bar chart showing ratio bars for 179.art]			
183.earthquake	1300	93.1	1396	87.4	1488	[Bar chart showing ratio bars for 183.earthquake]			
187.facerec	1900	94.0	2021	90.1	2109	[Bar chart showing ratio bars for 187.facerec]			
188.amp	2200	195	1126	187	1174	[Bar chart showing ratio bars for 188.amp]			
189.lucas	2000	115	1735	98.9	2023	[Bar chart showing ratio bars for 189.lucas]			
191.fma3d	2100	161	1303	163	1291	[Bar chart showing ratio bars for 191.fma3d]			
200.sixtrack	1100	182	606	173	637	[Bar chart showing ratio bars for 200.sixtrack]			
301.apsi	2600	215	1212	199	1305	[Bar chart showing ratio bars for 301.apsi]			

Hardware

CPU: AMD Opteron 1210
CPU MHz: 1800
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1 chip
Parallel: No
Primary Cache: 64KBI + 64KBD (on chip) per core
Secondary Cache: 1024KB (I+D) (on chip) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1GB, PC2-5300
Disk Subsystem: SATA, 80GB 10K RPM
Other Hardware: None

Software

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp
Compiler: PathScale EKO Compiler Suite, Release 2.4
PathScale EKOPATH(TM) Compiler Suite, Release 2.4
File System: Linux/reiserfs
System State: Multi-user, run level 3

Notes/Tuning Information

+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata

Baseline optimization

C programs: -Ofast -WOPT:mem_opnds=on +FDO
Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on +FDO
Portability Flags:
178.galgel: -fixedform

Peak Tuning:

168.wupwise: -Ofast -IPA:linear=on -LNO:prefetch Ahead=5:prefetch=3
-OPT:unroll_times_max=8:unroll_size=128:IEEE_NaN_Inf=off:ro=3
171.swim: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_arith=3:unroll_size=200
-LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2
-WOPT:mem_opnds=on:aggstr=0
173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
-LNO:fusion=2:fission=2:full_unroll_size=10000 +FDO



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System X 3105 (AMD Opteron (TM) 1210)

SPECfp2000 = 1678
SPECfp_base2000 = 1546

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel:    -Ofast -OPT:fast_complex=on +FDO
179.art:       -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.quake:    -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec:  -Ofast -IPA:plimit=1500 -LNO:fusion=2
              -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 +FDO
188.ampp:     -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
              -GRA:optimize_boundary=on -fno-math-errno -TENV:X=4 +FDO
189.lucas:    -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d:    -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
              -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:early_intrinsics=on
              -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:     -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```