



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Ultra 25

SPECfp2000 = 1108

SPECfp\_base2000 = 1041

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jun-2006 Hardware Avail: Jun-2006 Software Avail: Jan-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	138	1161	135	1188
171.swim	3100	208	1492	204	1520
172.mgrid	1800	296	608	296	608
173.applu	2100	227	926	200	1049
177.mesa	1400	188	744	162	863
178.galgel	2900	166	1751	144	2020
179.art	2600	29.3	8883	26.0	9990
183.earthquake	1300	92.3	1408	86.2	1509
187.facerec	1900	124	1534	121	1568
188.amp	2200	448	491	420	524
189.lucas	2000	294	680	294	680
191.fma3d	2100	363	578	329	639
200.sixtrack	1100	223	492	214	513
301.apsi	2600	341	762	341	762

### Hardware

CPU: UltraSPARC IIIi  
 CPU MHz: 1336  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
 CPU(s) orderable: 1  
 Parallel: No  
 Primary Cache: 32KBI+64KBD per chip (on chip)  
 Secondary Cache: 1MB(I+D) per chip (on chip)  
 L3 Cache: None  
 Other Cache: None  
 Memory: 4GB(4x1GB DDR333 ECC REG)  
 Disk Subsystem: SATA,80GB,7200RPM  
 Other Hardware: None

### Software

Operating System: Solaris 10 1/06  
 Compiler: Sun Studio 11  
 File System: ufs (default ufs logging on with Solaris 10)  
 System State: Multi-User

## Notes/Tuning Information

Compiler invocation:

C: cc  
 F90: f90  
 F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias\_level=std with ONESTEP=yes and feedback  
 F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1  
 171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6  
 -Qoption iropt -Atile:skewp,-Ainline:cs=700  
 (no feedback)  
 172.mgrid: basepeak = yes



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Ultra 25

SPECfp2000 = 1108

SPECfp\_base2000 = 1041

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: Jan-2006

## Notes/Tuning Information (Continued)

```

173.applu:  -fast -xipo=2
            -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
            -Qoption iropt -Aujam:inner=g
177.mesa:   -fast -xipo=2 -xalias_level=strong -xrestrict
            -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
            RM_SOURCES=lapak.f90
179.art:    -fast -xipo=2 -xalias_level=std -xprefetch=latx:1.5
183.quake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2 -xprefetch=latx:1.5
188.ammp:   -fast -xarch=v9b -xipo=2 -xalias_level=std -lmopt -lm
189.lucas:  basepeak=yes
191.fma3d:  -fast -xipo=2 -stackvar -xprefetch_level=3
            -Qoption iropt -Apf:pdl=1
            -xO4 -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2 -xprefetch=no
301.apsi:   -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

178.galgel: -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```