



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 520Q (1650 Mhz, 4 CPU, SLES)

SPECfp\_rate2000 = 99.0

SPECfp\_rate\_base2000 = 92.9

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Aug-2006 | Software Avail: Dec-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	112	132	8	102	146
171.swim	8	335	85.9	8	327	87.9
172.mgrid	8	239	69.8	8	213	78.5
173.applu	8	341	57.1	8	312	62.5
177.mesa	8	195	66.6	8	195	66.6
178.galgel	8	157	172	8	126	214
179.art	8	51.7	467	8	47.7	505
183.equake	8	80.9	149	8	71.1	170
187.facerec	8	163	108	8	163	108
188.amp	8	360	56.7	8	365	56.0
189.lucas	8	284	65.3	8	272	68.3
191.fma3d	8	291	67.0	8	270	72.3
200.sixtrack	8	218	46.8	8	212	48.2
301.apsi	8	306	78.9	8	308	78.3

### Hardware

CPU: POWER5+  
 CPU MHz: 1650  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (SMT on)  
 CPU(s) orderable: 4 core  
 Parallel: No  
 Primary Cache: 64 KB I + 32 KB D on chip per core  
 Secondary Cache: 1920 KB I+D on chip per chip  
 L3 Cache: 36 MB I+D off chip per chip  
 Other Cache: None  
 Memory: 16 GB (8x2GB)  
 Disk Subsystem: 1x73GB SCSI, 15K RPM  
 Other Hardware: None

### Software

Operating System: SLES  
 SUSE Linux Enterprise Server 10 (ppc) VERSION = 10  
 w/2.6.16.21-0.8-ppc64 Linux kernel  
 Compiler: IBM XL C/C++ Advanced Edition V8.0.1 for Linux  
 IBM XL Fortran Advanced Edition V10.1.1 for Linux  
 Other software:  
 - IBM Engineering and Scientific Subroutine  
 Library (ESSL) for Linux - Version 4.2.5  
 File System: reiserfs  
 System State: Multi-User

## Notes/Tuning Information

+FDO  
 Feedback directed optimization enabled by: PASS1=-qpdf1 PASS2=-qpdf2

FP compilers  
 C: invoked as xlc  
 Fortran 77 and Fortran 90: invoked as xlf90, except as noted below

FP Portability Flags  
 -qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu,  
 178.galgel, 200.sixtrack, 301.apsi  
 -qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

FP Base Optimization Flags:  
 C: +FDO -O5  
 Fortran: +FDO -O5



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 520Q (1650 Mhz, 4 CPU, SLES)

SPECfp\_rate2000 = 99.0

SPECfp\_rate\_base2000 = 92.9

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Aug-2006 | Software Avail: Dec-2006

## Notes/Tuning Information (Continued)

Floating Point Peak Flags

```
168.wupwise
  +FDO -O5 -qsave -lmass
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
171.swim
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
172.mgrid
  +FDO -O4 -q64
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
173.applu
  +FDO -O5 -q64
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
177.mesa
  basepeak=1
178.galgel
  Fortran invoked as xlf90_r
  +FDO -O5 -qessl -lessl -lmass
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
179.art
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
183.quake
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
187.facerec
  basepeak=1
188.amp
  +FDO -O3 -qalign=linuxppc
189.lucas
  +FDO -O3 -qarch=auto -qtune=auto
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
191.fma3d
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
200.sixtrack
  +FDO -O3 -qarch=auto -qtune=auto
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
301.apsi
  Fortran invoked as xlf90_r
  +FDO -O5 -qessl
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
  extra_libs = -lessl
```

System Settings:

```
-- ulimit stack size set to unlimited
```

SMT: Acronym for 'Simultaneous Multi-Threading'. A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. SMT is enabled by default.

Large pages reserved as follows by root user:

```
echo 240 > /proc/sys/vm/nr_hugepages
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 520Q (1650 Mhz, 4 CPU, SLES)

SPECfp\_rate2000 = 99.0

SPECfp\_rate\_base2000 = 92.9

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Aug-2006 | Software Avail: Dec-2006

## Notes/Tuning Information (Continued)

System configured with libhugetlbfs library for application access to large pages  
Environment variables set as follows:  
export HUGETLB\_MORECORE=yes

Each process was bound to a cpu using submit= with the taskset command  
submit = taskset -p -c \\${SPECUSERNUM} \\${\\$} >/dev/null ; \$command