



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM System p5 550Q (1650 Mhz, 1 CPU, SLES)

SPECfp2000 = 2573
SPECfp_base2000 = 2157

SPEC license #: 11 Tested by: IBM Austin Test date: Oct-2006 Hardware Avail: Aug-2006 Software Avail: Dec-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	61.7	2593	53.2	3008
171.swim	3100	124	2501	97.4	3182
172.mgrid	1800	96.8	1860	74.5	2415
173.applu	2100	126	1666	94.7	2218
177.mesa	1400	128	1091	128	1091
178.galgel	2900	66.3	4377	41.0	7079
179.art	2600	23.3	11162	20.6	12638
183.quake	1300	29.3	4433	24.6	5276
187.facerec	1900	85.6	2220	85.6	2220
188.amp	2200	199	1104	196	1125
189.lucas	2000	75.5	2651	41.7	4795
191.fma3d	2100	158	1325	142	1480
200.sixtrack	1100	152	722	147	746
301.apsi	2600	163	1598	163	1597

Hardware

CPU: POWER5+
CPU MHz: 1650
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (SMT off)
CPU(s) orderable: 4,8 core
Parallel: No
Primary Cache: 64 KB I + 32 KB D on chip per core
Secondary Cache: 1920 KB I+D on chip per chip
L3 Cache: 36 MB I+D off chip per chip
Other Cache: None
Memory: 32 GB (16x2GB)
Disk Subsystem: 1x73GB SCSI, 15K RPM
Other Hardware: None

Software

Operating System: SLES
SUSE Linux Enterprise Server 10 (ppc) VERSION = 10
w/2.6.16.21-0.8-ppc64 Linux kernel
Compiler: IBM XL C/C++ Advanced Edition V8.0.1 for Linux
IBM XL Fortran Advanced Edition V10.1.1 for Linux
Other software:
- IBM Engineering and Scientific Subroutine
Library (ESSL) for Linux - Version 4.2.5
File System: reiserfs
System State: Multi-User

Notes/Tuning Information

+FDO
Feedback directed optimization enabled by: PASS1=-qpdf1 PASS2=-qpdf2

FP compilers
C: invoked as xlc
Fortran 77 and Fortran 90: invoked as xlf90, except as noted below

FP Portability Flags
-qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu,
178.galgel, 200.sixtrack, 301.apsi
-qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

FP Base Optimization Flags:
C: +FDO -O5
Fortran: +FDO -O5



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 550Q (1650 Mhz, 1 CPU, SLES)

SPECfp2000 = 2573

SPECfp_base2000 = 2157

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Aug-2006 | Software Avail: Dec-2006

Notes/Tuning Information (Continued)

Floating Point Peak Flags

```
168.wupwise
  +FDO -O5 -qsave -lmass
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
171.swim
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
172.mgrid
  +FDO -O4 -q64
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
173.applu
  +FDO -O5 -q64
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
177.mesa
  basepeak=1
178.galgel
  Fortran invoked as xlf90_r
  +FDO -O5 -qessl -lessl -lmass
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
179.art
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
183.quake
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
187.facerec
  basepeak=1
188.amp
  +FDO -O3 -qalign=linuxppc
189.lucas
  +FDO -O3 -qarch=auto -qtune=auto
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
191.fma3d
  +FDO -O5
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
200.sixtrack
  +FDO -O3 -qarch=auto -qtune=auto
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
301.apsi
  Fortran invoked as xlf90_r
  +FDO -O5 -qessl
  -B/usr/share/libhugetlbfs/ -t1 -Wl,--hugetlbfs-link=BDT
  extra_libs = -lessl
```

System Settings:

```
-- ulimit stack size set to unlimited
```

SMT: Acronym for 'Simultaneous Multi-Threading'. A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. SMT is enabled by default.

Large pages reserved as follows by root user:

```
echo 30 > /proc/sys/vm/nr_hugepages
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 550Q (1650 Mhz, 1 CPU, SLES)

SPECfp2000 = 2573

SPECfp_base2000 = 2157

SPEC license #: 11 | Tested by: IBM Austin | Test date: Oct-2006 | Hardware Avail: Aug-2006 | Software Avail: Dec-2006

Notes/Tuning Information (Continued)

System configured with libhugetlbfs library for application access to large pages

Environment variables set as follows:

```
export HUGETLB_MORECORE=yes
```

Linux booted with the options:

```
maxcpus=1 smt-enabled=off
```

Each process was bound to a cpu using submit= with the taskset command

```
submit = taskset -p -c \${SPECUSERNUM} \${\$} >/dev/null ; \$command
```