



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec MX201 (Intel Xeon 5110 processor, 1.86GHz)

SPECfp_rate2000 = 54.4

SPECfp_rate_base2000 = 54.4

SPEC license #: 9001 | Tested by: Itaotec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	92.5	80.3	4	92.5	80.3
171.swim	4	361	39.8	4	361	39.8
172.mgrid	4	265	31.5	4	265	31.5
173.applu	4	239	40.8	4	239	40.8
177.mesa	4	96.9	67.0	4	96.9	67.0
178.galgel	4	93.8	144	4	93.8	144
179.art	4	83.3	145	4	83.3	145
183.equake	4	112	54.1	4	112	54.1
187.facerec	4	135	65.2	4	135	65.2
188.amp	4	234	43.6	4	234	43.6
189.lucas	4	221	42.1	4	221	42.1
191.fma3d	4	238	40.9	4	238	40.9
200.sixtrack	4	175	29.2	4	175	29.2
301.apsi	4	271	44.5	4	271	44.5

Hardware

CPU: Intel Xeon 5110 processor (1.60 GHz, 4MB L2 shared, 1333 MHz system bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4096KB(I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)ECC
Disk Subsystem: 1 x 36GB U320 SCSI 10000 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Intel Fortran Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio 2003(for libraries)
MicroQuill SmartHeap for SMP Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

178.galgel: -FI /F32000000

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO

for C programs: -fast +FDO shlSMPMt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>