



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec

Servidor Itautec LX211 (Intel Xeon 5110 processor, 1.86GHz)

SPECfp_rate2000 = 30.2

SPECfp_rate_base2000 = 30.2

SPEC license #: 9001 | Tested by: Itautec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	78.3	47.4	2	78.3	47.4
171.swim	2	275	26.1	2	275	26.1
172.mgrid	2	196	21.3	2	196	21.3
173.applu	2	202	24.1	2	202	24.1
177.mesa	2	98.5	33.0	2	98.5	33.0
178.galgel	2	91.0	73.9	2	91.0	73.9
179.art	2	78.9	76.5	2	78.9	76.5
183.equake	2	88.9	33.9	2	88.9	33.9
187.facerec	2	132	33.4	2	132	33.4
188.amp	2	240	21.3	2	240	21.3
189.lucas	2	197	23.6	2	197	23.6
191.fma3d	2	210	23.2	2	210	23.2
200.sixtrack	2	174	14.6	2	174	14.6
301.apsi	2	259	23.3	2	259	23.3

Hardware

CPU: Intel Xeon 5110 processor (1.60 GHz, 4MB L2 shared, 1066 MHz system bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4096KB(I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 6x2GB DDR2-RAM PC2-5300F (CAS 5-5-5)ECC
Disk Subsystem: 1 x 120GB Serial ATA 7200 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060519Z (for 32-bit applications),
Intel Fortran Compiler 9.1
Build 20060519Z (for 32-bit applications),
Microsoft Visual Studio 2005 (for libraries),
MicroQuill SmartHeap for SMP Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

178.galgel: -FI /F32000000

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO

for C programs: -fast +FDO shlSMPMt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>