



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3650 (1.6 GHz Xeon E5310, 8MB L2 Cache)

SPECfp2000 = --

SPECfp_base2000 = 1627

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	68.6	2333		
171.swim	3100	149	2086		
172.mgrid	1800	172	1045		
173.applu	2100	168	1248		
177.mesa	1400	90.7	1543		
178.galgel	2900	74.7	3881		
179.art	2600	46.8	5552		
183.quake	1300	63.2	2056		
187.facerec	1900	120	1581		
188.amp	2200	188	1172		
189.lucas	2000	139	1436		
191.fma3d	2100	172	1220		
200.sixtrack	1100	172	641		
301.apsi	2600	258	1007		

Hardware

CPU: Intel Xeon processor E5310 (1.6 GHz, 1066 MHz bus)
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1, 2 chips
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024 MB ECC PC2-5300F
 Disk Subsystem: 73GB SAS 15K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
```