



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 2950 (Intel Xeon processor E5310, 1.60 GHz)

SPECint_rate2000 = 132

SPECint_rate_base2000 = 132

SPEC license #: 55 | Tested by: Dell, Inc., Round Rock, TX | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	147	88.7	8	147	88.5
175.vpr	8	134	96.7	8	133	98.0
176.gcc	8	67.1	152	8	67.1	152
181.mcf	8	159	105	8	159	105
186.crafty	8	68.6	135	8	68.7	135
197.parser	8	149	112	8	148	113
252.eon	8	62.2	194	8	62.4	193
253.perlbnk	8	95.3	175	8	95.3	175
254.gap	8	96.8	105	8	95.8	107
255.vortex	8	77.3	228	8	77.3	228
256.bzip2	8	142	98.3	8	141	99.0
300.twolf	8	164	170	8	164	170

Hardware

CPU: Quad-Core Intel Xeon processor E5310 (1066 MHz system bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 8 MB I+D on chip, per chip (4 MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 GB (8 x 1 GB 667 MHz CL5 FB-DIMM DDR2 SDRAM)
Disk Subsystem: 1 x 80GB SATA 7200 RPM
Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ Compiler 9.1 for IA32(20060519Z)
Microsoft Visual Studio .NET 2003(7.1.3088)
MicroQuill SmartHeap Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast +FDO shlw32M.lib
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Oa +FDO shlw32M.lib
197.parser: -fast +FDO
252.eon: -fast +FDO
253.perlbnk: basepeak=yes



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 2950 (Intel Xeon processor E5310, 1.60 GHz)

SPECint_rate2000 = 132

SPECint_rate_base2000 = 132

SPEC license #: 55 | Tested by: Dell, Inc., Round Rock, TX | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
254.gap:      -fast +FDO
255.vortex    basepeak=yes
256.bzip2:    -fast -Qunroll11 -Oa +FDO
300.twolf:    basepeak=yes
BIOS SETTINGS
  Adjacent Cache Line Prefetch disabled in BIOS
```