



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 2950 (Intel Xeon processor E5335, 2.00 GHz)

SPECint_rate2000 = 165

SPECint_rate_base2000 = 165

SPEC license #: 55 | Tested by: Dell, Inc., Round Rock, TX | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	117	111	8	117	111
175.vpr	8	108	120	8	107	122
176.gcc	8	53.8	190	8	53.8	190
181.mcf	8	128	130	8	128	130
186.crafty	8	54.9	169	8	55.0	169
197.parser	8	119	140	8	119	140
252.eon	8	49.8	242	8	49.8	242
253.perlbnk	8	75.5	221	8	75.5	221
254.gap	8	76.6	133	8	76.7	133
255.vortex	8	62.4	282	8	62.4	282
256.bzip2	8	112	124	8	115	121
300.twolf	8	132	212	8	132	212

Hardware

CPU: Quad-Core Intel Xeon processor E5335 (1333 MHz system bus)
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 8 MB I+D on chip, per chip (4 MB shared per 2 cores)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 GB (8 x 1 GB 667 MHz CL5 FB-DIMM DDR2 SDRAM)
 Disk Subsystem: 1 x 80GB SATA 7200 RPM
 Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
 Compiler: Intel C++ Compiler 9.1 for IA32(20060519Z)
 Microsoft Visual Studio .NET 2003(7.1.3088)
 MicroQuill SmartHeap Library 8.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast +FDO shlw32m.lib
 C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
 175.vpr: -fast +FDO
 176.gcc: basepeak=yes
 181.mcf: basepeak=yes
 186.crafty: -fast -Oa +FDO shlw32m.lib
 197.parser: -fast +FDO
 252.eon: -fast +FDO
 253.perlbnk: basepeak=yes



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 2950 (Intel Xeon processor E5335, 2.00 GHz)

SPECint_rate2000 = 165

SPECint_rate_base2000 = 165

SPEC license #: 55 | Tested by: Dell, Inc., Round Rock, TX | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
254.gap:      -fast +FDO
255.vortex    basepeak=yes
256.bzip2:    -fast -Qunroll11 -Oa +FDO
300.twolf:    basepeak=yes
BIOS SETTINGS
  Adjacent Cache Line Prefetch disabled in BIOS
```