



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant DL365 (AMD Opteron (TM) 2220SE)

SPECint\_rate2000 = **86.0**  
SPECint\_rate\_base2000 = **75.9**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Oct-2006 Hardware Avail: Jan-2007 Software Avail: Sep-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	83.0	78.2	4	82.8	78.4
175.vpr	4	110	59.1	4	104	62.6
176.gcc	4	58.2	87.6	4	58.8	86.8
181.mcf	4	293	28.5	4	176	47.5
186.crafty	4	42.3	110	4	42.0	111
197.parser	4	143	58.4	4	112	74.7
252.eon	4	43.8	138	4	39.3	153
253.perlbnk	4	102	82.1	4	85.4	97.8
254.gap	4	64.5	79.1	4	63.1	80.9
255.vortex	4	73.2	120	4	66.3	133
256.bzip2	4	101	69.2	4	101	69.2
300.twolf	4	210	66.2	4	159	87.8

### Hardware

CPU: AMD Opteron (TM) 2220SE  
CPU MHz: 2800  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 64 KB I + 64 KB D on chip per core  
Secondary Cache: 1 MB I+D on chip per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 16 GB (8x2 GB PC2-5300P CL5.0)  
Disk Subsystem: 1x36 GB 10 K SAS  
Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 3  
SuSE kernel 2.6.5-7.244-smp  
Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.5  
File System: Linux/ext2  
System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -Ofast +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_LP64
254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
-DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
255.vortex: -DSPEC_CPU2000_LP64
Peak tuning:
164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
175.vpr: -O3 -ipa -m32 +FDO
176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
-OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL365 (AMD Opteron (TM) 2220SE)

SPECint\_rate2000 = 86.0  
SPECint\_rate\_base2000 = 75.9

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Oct-2006 | Hardware Avail: Jan-2007 | Software Avail: Sep-2006

## Notes/Tuning Information (Continued)

```
-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak=true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO
```

### BIOS Configuration Notes

Node Interleaving Disabled

### Other Configuration Notes

Taskset utility used to bind process to CPU(s)